

[MC-NBFS]: .NET Binary Format: SOAP Data Structure

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
08/10/2007	0.1	Major	Initial Availability
09/28/2007	0.2	Minor	Updated the technical content.
10/23/2007	0.2.1	Editorial	Revised and edited the technical content.
11/30/2007	0.3	Minor	Updated the technical content.
01/25/2008	0.3.1	Editorial	Revised and edited the technical content.
03/14/2008	0.3.2	Editorial	Revised and edited the technical content.
05/16/2008	0.3.3	Editorial	Revised and edited the technical content.
06/20/2008	0.3.4	Editorial	Revised and edited the technical content.
07/25/2008	0.3.5	Editorial	Revised and edited the technical content.
08/29/2008	0.3.6	Editorial	Revised and edited the technical content.
10/24/2008	0.3.7	Editorial	Revised and edited the technical content.
12/05/2008	0.4	Minor	Updated the technical content.
01/16/2009	0.4.1	Editorial	Revised and edited the technical content.
02/27/2009	0.4.2	Editorial	Revised and edited the technical content.
04/10/2009	0.4.3	Editorial	Revised and edited the technical content.
05/22/2009	0.5	Minor	Updated the technical content.
07/02/2009	0.5.1	Editorial	Revised and edited the technical content.
08/14/2009	0.5.2	Editorial	Revised and edited the technical content.
09/25/2009	0.6	Minor	Updated the technical content.
11/06/2009	0.6.1	Editorial	Revised and edited the technical content.
12/18/2009	0.6.2	Editorial	Revised and edited the technical content.
01/29/2010	0.6.3	Editorial	Revised and edited the technical content.
03/12/2010	0.6.4	Editorial	Revised and edited the technical content.
04/23/2010	1.0	Major	Updated and revised the technical content.
06/04/2010	1.0.1	Editorial	Revised and edited the technical content.
07/16/2010	2.0	Major	Significantly changed the technical content.

Date	Revision History	Revision Class	Comments
08/27/2010	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2010	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	2.1	Minor	Clarified the meaning of the technical content.

Contents

1	Introduction	5
1.1	Glossary	5
1.2	References.....	5
1.2.1	Normative References.....	5
1.2.2	Informative References	6
1.3	Overview	6
1.4	Relationship to Protocols and Other Structures	6
1.5	Applicability Statement.....	6
1.6	Versioning and Localization	6
1.7	Vendor-Extensible Fields.....	6
2	Structures	7
2.1	DictionaryString	7
3	Structure Examples	24
4	Security Considerations.....	26
5	Appendix A: Product Behavior	27
6	Change Tracking.....	28
7	Index	30

1 Introduction

This specification defines the .NET Binary Format: SOAP Data Structure, which is a new format built by extending the format described in the .NET Binary Format: **XML** Data Structure, as specified in [\[MC-NBFX\]](#). While the SOAP data structure is structurally identical to the XML data structure, should not be used where an XML data structure document is expected.

The XML Data Structure specifies a binary XML format to efficiently encode the structures that are common to any XML document. The SOAP protocol specifies an XML document with specific structures that are common to many SOAP messages. While using XML Data Structure alone to encode SOAP messages provides efficiencies for the structures of XML, one can observe that strings common to many SOAP messages are still encoded in their entirety. Furthermore, the XML data structure does not specify how a producer and a consumer of a document agree on the strings referenced within a document.

The purpose of the SOAP data structure is to extend the XML data structure format to further reduce the cost of generating SOAP documents by defining a shortened structure of strings to which a producer and a consumer can refer.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

.NET Framework
XML

The following terms are defined in [\[MC-NBFX\]](#):

DictionaryString
MultiByteInt31
record
string

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MC-NBFSE] Microsoft Corporation, "[.NET Binary Format: SOAP Extension](#)".

[MC-NBFX] Microsoft Corporation, "[.NET Binary Format: XML Data Structure](#)".

[MC-NMF] Microsoft Corporation, "[.NET Message Framing Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[SOAP1.2-1/2007] Gudgin, M., Hadley, M., Mendelsohn, N., et al., "SOAP Version 1.2 Part 1: Messaging Framework (Second Edition) ", W3C Recommendation 27, April 2007, <http://www.w3.org/TR/2007/REC-soap12-part1-20070427/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

1.3 Overview

The .NET Binary Format: SOAP Data Structure is used to efficiently represent SOAP documents, as specified in [\[SOAP1.2-1/2007\]](#).

1.4 Relationship to Protocols and Other Structures

The .NET Binary Format: SOAP Data Structure extends the .NET Binary Format: XML Data Structure, as specified in [\[MC-NBFX\]](#). The .NET Binary Format: SOAP Extension, as specified in [\[MC-NBFSE\]](#), and the .NET Message Framing Protocol, as specified in [\[MC-NMF\]](#), both use the .NET Binary Format: SOAP Data Structure.

1.5 Applicability Statement

The .NET Binary Format: SOAP Data Structure is a general-purpose way to represent an XML document and is applied as specified in [\[MC-NBFX\]](#) section 1.3. Additionally, the format is particularly well-suited for SOAP documents as specified in [\[SOAP1.2-1/2007\]](#) because it defines a fixed set of s from the SOAP vocabulary that a producer and a consumer of documents in this format may reference and results in smaller documents.

This specification extends the format described by [\[MC-NBFX\]](#), which describes an efficient encoding for general XML documents. This specification describes efficient encoding for strings that are specific to SOAP messages and does not supersede any of the structures defined in [\[MC-NBFX\]](#).

1.6 Versioning and Localization

For information on versioning and localization, see [\[MC-NBFX\]](#) section 1.3.

1.7 Vendor-Extensible Fields

The .NET Binary Format: SOAP Data Structure has no vendor-extensible fields.

2 Structures

The structures in the .NET Binary Format: SOAP Data Structure are identical to those specified in [\[MC-NBFX\]](#), except that the [DictionaryString](#) structure, as defined in [\[MC-NBFX\]](#) section 1.3, has an additional meaning, described in the following section.

2.1 DictionaryString

The DictionaryString structure describes a reference to a set of characters. This specification lists a static set of characters that both producer and consumer can map via the DictionaryString structure.

The DictionaryString structure MUST be an even integer value. This restriction exists such that another specification, namely [\[MC-NBFSE\]](#), may define the odd integers to reference another list of sets of characters.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Value (variable)																															

Value: An even integer value encoded by using **MultiByteInt31**. The value MUST be one of the values shown in the first column of the following table. The characters represented by this data structure MUST correspond to the characters—exactly as they are shown—in the second column of the following table. Even values not appearing in the following table have no character representation and are reserved.

Value	Characters
0x00	mustUnderstand
0x02	Envelope
0x04	http://www.w3.org/2003/05/soap-envelope
0x06	http://www.w3.org/2005/08/addressing
0x08	Header
0x0A	Action
0x0C	To
0x0E	Body
0x10	Algorithm
0x12	RelatesTo
0x14	http://www.w3.org/2005/08/addressing/anonymous
0x16	URI
0x18	Reference
0x1A	MessageID

Value	Characters
0x1C	Id
0x1E	Identifier
0x20	http://schemas.xmlsoap.org/ws/2005/02/rm
0x22	Transforms
0x24	Transform
0x26	DigestMethod
0x28	DigestValue
0x2A	Address
0x2C	ReplyTo
0x2E	SequenceAcknowledgement
0x30	AcknowledgementRange
0x32	Upper
0x34	Lower
0x36	BufferRemaining
0x38	http://schemas.microsoft.com/ws/2006/05/rm
0x3A	http://schemas.xmlsoap.org/ws/2005/02/rm/SequenceAcknowledgement
0x3C	SecurityTokenReference
0x3E	Sequence
0x40	MessageNumber
0x42	http://www.w3.org/2000/09/xmldsig#
0x44	http://www.w3.org/2000/09/xmldsig#enveloped-signature
0x46	KeyInfo
0x48	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd
0x4A	http://www.w3.org/2001/04/xmlenc#
0x4C	http://schemas.xmlsoap.org/ws/2005/02/sc
0x4E	DerivedKeyToken
0x50	Nonce
0x52	Signature
0x54	SignedInfo
0x56	CanonicalizationMethod

Value	Characters
0x58	SignatureMethod
0x5A	SignatureValue
0x5C	DataReference
0x5E	EncryptedData
0x60	EncryptionMethod
0x62	CipherData
0x64	CipherValue
0x66	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd
0x68	Security
0x6A	Timestamp
0x6C	Created
0x6E	Expires
0x70	Length
0x72	ReferenceList
0x74	ValueType
0x76	Type
0x78	EncryptedHeader
0x7A	http://docs.oasis-open.org/wss/oasis-wss-wssecurity-secext-1.1.xsd
0x7C	RequestSecurityTokenResponseCollection
0x7E	http://schemas.xmlsoap.org/ws/2005/02/trust
0x80	http://schemas.xmlsoap.org/ws/2005/02/trust#BinarySecret
0x82	http://schemas.microsoft.com/ws/2006/02/transactions
0x84	s
0x86	Fault
0x88	MustUnderstand
0x8A	role
0x8C	relay
0x8E	Code
0x90	Reason
0x92	Text

Value	Characters
0x94	Node
0x96	Role
0x98	Detail
0x9A	Value
0x9C	Subcode
0x9E	NotUnderstood
0xA0	qname
0xA2	
0xA4	From
0xA6	FaultTo
0xA8	EndpointReference
0xAA	PortType
0xAC	ServiceName
0xAE	PortName
0xB0	ReferenceProperties
0xB2	RelationshipType
0xB4	Reply
0xB6	a
0xB8	http://schemas.xmlsoap.org/ws/2006/02/addressingidentity
0xBA	Identity
0xBC	Spn
0xBE	Upn
0xC0	Rsa
0xC2	Dns
0xC4	X509v3Certificate
0xC6	http://www.w3.org/2005/08/addressing/fault
0xC8	ReferenceParameters
0xCA	IsReferenceParameter
0xCC	http://www.w3.org/2005/08/addressing/reply
0xCE	http://www.w3.org/2005/08/addressing/none

Value	Characters
0xD0	Metadata
0xD2	http://schemas.xmlsoap.org/ws/2004/08/addressing
0xD4	http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous
0xD6	http://schemas.xmlsoap.org/ws/2004/08/addressing/fault
0xD8	http://schemas.xmlsoap.org/ws/2004/06/addressingex
0xDA	RedirectTo
0xDC	Via
0xDE	http://www.w3.org/2001/10/xml-exc-c14n#
0xE0	PrefixList
0xE2	InclusiveNamespaces
0xE4	ec
0xE6	SecurityContextToken
0xE8	Generation
0xEA	Label
0xEC	Offset
0xEE	Properties
0xF0	Cookie
0xF2	wsc
0xF4	http://schemas.xmlsoap.org/ws/2004/04/sc
0xF6	http://schemas.xmlsoap.org/ws/2004/04/security/sc/dk
0xF8	http://schemas.xmlsoap.org/ws/2004/04/security/sc/sct
0xFA	http://schemas.xmlsoap.org/ws/2004/04/security/trust/RST/SCT
0xFC	http://schemas.xmlsoap.org/ws/2004/04/security/trust/RSTR/SCT
0xFE	RenewNeeded
0x100	BadContextToken
0x102	c
0x104	http://schemas.xmlsoap.org/ws/2005/02/sc/dk
0x106	http://schemas.xmlsoap.org/ws/2005/02/sc/sct
0x108	http://schemas.xmlsoap.org/ws/2005/02/trust/RST/SCT
0x10A	http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/SCT

Value	Characters
0x10C	http://schemas.xmlsoap.org/ws/2005/02/trust/RST/SCT/Renew
0x10E	http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/SCT/Renew
0x110	http://schemas.xmlsoap.org/ws/2005/02/trust/RST/SCT/Cancel
0x112	http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/SCT/Cancel
0x114	http://www.w3.org/2001/04/xmlenc#aes128-cbc
0x116	http://www.w3.org/2001/04/xmlenc#kw-aes128
0x118	http://www.w3.org/2001/04/xmlenc#aes192-cbc
0x11A	http://www.w3.org/2001/04/xmlenc#kw-aes192
0x11C	http://www.w3.org/2001/04/xmlenc#aes256-cbc
0x11E	http://www.w3.org/2001/04/xmlenc#kw-aes256
0x120	http://www.w3.org/2001/04/xmlenc#des-cbc
0x122	http://www.w3.org/2000/09/xmldsig#dsa-sha1
0x124	http://www.w3.org/2001/10/xml-exc-c14n#WithComments
0x126	http://www.w3.org/2000/09/xmldsig#hmac-sha1
0x128	http://www.w3.org/2001/04/xmldsig-more#hmac-sha256
0x12A	http://schemas.xmlsoap.org/ws/2005/02/sc/dk/p_sha1
0x12C	http://www.w3.org/2001/04/xmlenc#ripemd160
0x12E	http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p
0x130	http://www.w3.org/2000/09/xmldsig#rsa-sha1
0x132	http://www.w3.org/2001/04/xmldsig-more#rsa-sha256
0x134	http://www.w3.org/2001/04/xmlenc#rsa-1_5
0x136	http://www.w3.org/2000/09/xmldsig#sha1
0x138	http://www.w3.org/2001/04/xmlenc#sha256
0x13A	http://www.w3.org/2001/04/xmlenc#sha512
0x13C	http://www.w3.org/2001/04/xmlenc#tripledes-cbc
0x13E	http://www.w3.org/2001/04/xmlenc#kw-tripledes
0x140	http://schemas.xmlsoap.org/2005/02/trust/tlsnego#TLS_Wrap
0x142	http://schemas.xmlsoap.org/2005/02/trust/spnego#GSS_Wrap
0x144	http://schemas.microsoft.com/ws/2006/05/security
0x146	dnse

Value	Characters
0x148	o
0x14A	Password
0x14C	PasswordText
0x14E	Username
0x150	UsernameToken
0x152	BinarySecurityToken
0x154	EncodingType
0x156	KeyIdentifier
0x158	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary
0x15A	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#HexBinary
0x15C	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Text
0x15E	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#X509SubjectKeyIdentifier
0x160	http://docs.oasis-open.org/wss/oasis-wss-kerberos-token-profile-1.1#GSS_Kerberosv5_AP_REQ
0x162	http://docs.oasis-open.org/wss/oasis-wss-kerberos-token-profile-1.1#GSS_Kerberosv5_AP_REQ1510
0x164	http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.0#SAMLAssertionID
0x166	Assertion
0x168	urn:oasis:names:tc:SAML:1.0:assertion
0x16A	http://docs.oasis-open.org/wss/oasis-wss-rel-token-profile-1.0.pdf#license
0x16C	FailedAuthentication
0x16E	InvalidSecurityToken
0x170	InvalidSecurity
0x172	k
0x174	SignatureConfirmation
0x176	TokenType
0x178	http://docs.oasis-open.org/wss/oasis-wss-soap-message-security-1.1#ThumbprintSHA1
0x17A	http://docs.oasis-open.org/wss/oasis-wss-soap-message-security-1.1#EncryptedKey
0x17C	http://docs.oasis-open.org/wss/oasis-wss-soap-message-security-1.1#EncryptedKeySHA1

Value	Characters
0x17E	http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV1.1
0x180	http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV2.0
0x182	http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLID
0x184	AUTH-HASH
0x186	RequestSecurityTokenResponse
0x188	KeySize
0x18A	RequestedTokenReference
0x18C	AppliesTo
0x18E	Authenticator
0x190	CombinedHash
0x192	BinaryExchange
0x194	Lifetime
0x196	RequestedSecurityToken
0x198	Entropy
0x19A	RequestedProofToken
0x19C	ComputedKey
0x19E	RequestSecurityToken
0x1A0	RequestType
0x1A2	Context
0x1A4	BinarySecret
0x1A6	http://schemas.xmlsoap.org/ws/2005/02/trust/spnego
0x1A8	http://schemas.xmlsoap.org/ws/2005/02/trust/tlsnego
0x1AA	wst
0x1AC	http://schemas.xmlsoap.org/ws/2004/04/trust
0x1AE	http://schemas.xmlsoap.org/ws/2004/04/security/trust/RST/Issue
0x1B0	http://schemas.xmlsoap.org/ws/2004/04/security/trust/RSTR/Issue
0x1B2	http://schemas.xmlsoap.org/ws/2004/04/security/trust/Issue
0x1B4	http://schemas.xmlsoap.org/ws/2004/04/security/trust/CK/PSHA1
0x1B6	http://schemas.xmlsoap.org/ws/2004/04/security/trust/SymmetricKey
0x1B8	http://schemas.xmlsoap.org/ws/2004/04/security/trust/Nonce

Value	Characters
0x1BA	KeyType
0x1BC	http://schemas.xmlsoap.org/ws/2004/04/trust/SymmetricKey
0x1BE	http://schemas.xmlsoap.org/ws/2004/04/trust/PublicKey
0x1C0	Claims
0x1C2	InvalidRequest
0x1C4	RequestFailed
0x1C6	SignWith
0x1C8	EncryptWith
0x1CA	EncryptionAlgorithm
0x1CC	CanonicalizationAlgorithm
0x1CE	ComputedKeyAlgorithm
0x1D0	UseKey
0x1D2	http://schemas.microsoft.com/net/2004/07/secext/WS-SPNego
0x1D4	http://schemas.microsoft.com/net/2004/07/secext/TLSNego
0x1D6	t
0x1D8	http://schemas.xmlsoap.org/ws/2005/02/trust/RST/Issue
0x1DA	http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/Issue
0x1DC	http://schemas.xmlsoap.org/ws/2005/02/trust/Issue
0x1DE	http://schemas.xmlsoap.org/ws/2005/02/trust/SymmetricKey
0x1E0	http://schemas.xmlsoap.org/ws/2005/02/trust/CK/PSHA1
0x1E2	http://schemas.xmlsoap.org/ws/2005/02/trust/Nonce
0x1E4	RenewTarget
0x1E6	CancelTarget
0x1E8	RequestedTokenCancelled
0x1EA	RequestedAttachedReference
0x1EC	RequestedUnattachedReference
0x1EE	IssuedTokens
0x1F0	http://schemas.xmlsoap.org/ws/2005/02/trust/Renew
0x1F2	http://schemas.xmlsoap.org/ws/2005/02/trust/Cancel
0x1F4	http://schemas.xmlsoap.org/ws/2005/02/trust/PublicKey

Value	Characters
0x1F6	Access
0x1F8	AccessDecision
0x1FA	Advice
0x1FC	AssertionID
0x1FE	AssertionIDReference
0x200	Attribute
0x202	AttributeName
0x204	AttributeNamespace
0x206	AttributeStatement
0x208	AttributeValue
0x20A	Audience
0x20C	AudienceRestrictionCondition
0x20E	AuthenticationInstant
0x210	AuthenticationMethod
0x212	AuthenticationStatement
0x214	AuthorityBinding
0x216	AuthorityKind
0x218	AuthorizationDecisionStatement
0x21A	Binding
0x21C	Condition
0x21E	Conditions
0x220	Decision
0x222	DoNotCacheCondition
0x224	Evidence
0x226	IssueInstant
0x228	Issuer
0x22A	Location
0x22C	MajorVersion
0x22E	MinorVersion
0x230	NameIdentifier

Value	Characters
0x232	Format
0x234	NameQualifier
0x236	Namespace
0x238	NotBefore
0x23A	NotOnOrAfter
0x23C	saml
0x23E	Statement
0x240	Subject
0x242	SubjectConfirmation
0x244	SubjectConfirmationData
0x246	ConfirmationMethod
0x248	urn:oasis:names:tc:SAML:1.0:cm:holder-of-key
0x24A	urn:oasis:names:tc:SAML:1.0:cm:sender-vouches
0x24C	SubjectLocality
0x24E	DNSAddress
0x250	IPAddress
0x252	SubjectStatement
0x254	urn:oasis:names:tc:SAML:1.0:am:unspecified
0x256	xmlns
0x258	Resource
0x25A	UserName
0x25C	urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualifiedName
0x25E	EmailName
0x260	urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress
0x262	u
0x264	ChannelInstance
0x266	http://schemas.microsoft.com/ws/2005/02/duplex
0x268	Encoding
0x26A	MimeType
0x26C	CarriedKeyName

Value	Characters
0x26E	Recipient
0x270	EncryptedKey
0x272	KeyReference
0x274	e
0x276	http://www.w3.org/2001/04/xmlenc#Element
0x278	http://www.w3.org/2001/04/xmlenc#Content
0x27A	KeyName
0x27C	MgmtData
0x27E	KeyValue
0x280	RSAPublicValue
0x282	Modulus
0x284	Exponent
0x286	X509Data
0x288	X509IssuerSerial
0x28A	X509IssuerName
0x28C	X509SerialNumber
0x28E	X509Certificate
0x290	AckRequested
0x292	http://schemas.xmlsoap.org/ws/2005/02/rm/AckRequested
0x294	AcksTo
0x296	Accept
0x298	CreateSequence
0x29A	http://schemas.xmlsoap.org/ws/2005/02/rm/CreateSequence
0x29C	CreateSequenceRefused
0x29E	CreateSequenceResponse
0x2A0	http://schemas.xmlsoap.org/ws/2005/02/rm/CreateSequenceResponse
0x2A2	FaultCode
0x2A4	InvalidAcknowledgement
0x2A6	LastMessage
0x2A8	http://schemas.xmlsoap.org/ws/2005/02/rm/LastMessage

Value	Characters
0x2AA	LastMessageNumberExceeded
0x2AC	MessageNumberRollover
0x2AE	Nack
0x2B0	netrm
0x2B2	Offer
0x2B4	r
0x2B6	SequenceFault
0x2B8	SequenceTerminated
0x2BA	TerminateSequence
0x2BC	http://schemas.xmlsoap.org/ws/2005/02/rm/TerminateSequence
0x2BE	UnknownSequence
0x2C0	http://schemas.microsoft.com/ws/2006/02/tx/oletx
0x2C2	oletx
0x2C4	OleTxTransaction
0x2C6	PropagationToken
0x2C8	http://schemas.xmlsoap.org/ws/2004/10/wscoor
0x2CA	wscoor
0x2CC	CreateCoordinationContext
0x2CE	CreateCoordinationContextResponse
0x2D0	CoordinationContext
0x2D2	CurrentContext
0x2D4	CoordinationType
0x2D6	RegistrationService
0x2D8	Register
0x2DA	RegisterResponse
0x2DC	ProtocolIdentifier
0x2DE	CoordinatorProtocolService
0x2E0	ParticipantProtocolService
0x2E2	http://schemas.xmlsoap.org/ws/2004/10/wscoor/CreateCoordinationContext
0x2E4	http://schemas.xmlsoap.org/ws/2004/10/wscoor/CreateCoordinationContextResponse

Value	Characters
0x2E6	http://schemas.xmlsoap.org/ws/2004/10/wscoor/Register
0x2E8	http://schemas.xmlsoap.org/ws/2004/10/wscoor/RegisterResponse
0x2EA	http://schemas.xmlsoap.org/ws/2004/10/wscoor/fault
0x2EC	ActivationCoordinatorPortType
0x2EE	RegistrationCoordinatorPortType
0x2F0	InvalidState
0x2F2	InvalidProtocol
0x2F4	InvalidParameters
0x2F6	NoActivity
0x2F8	ContextRefused
0x2FA	AlreadyRegistered
0x2FC	http://schemas.xmlsoap.org/ws/2004/10/wsat
0x2FE	wsat
0x300	http://schemas.xmlsoap.org/ws/2004/10/wsat/Completion
0x302	http://schemas.xmlsoap.org/ws/2004/10/wsat/Durable2PC
0x304	http://schemas.xmlsoap.org/ws/2004/10/wsat/Volatile2PC
0x306	Prepare
0x308	Prepared
0x30A	ReadOnly
0x30C	Commit
0x30E	Rollback
0x310	Committed
0x312	Aborted
0x314	Replay
0x316	http://schemas.xmlsoap.org/ws/2004/10/wsat/Commit
0x318	http://schemas.xmlsoap.org/ws/2004/10/wsat/Rollback
0x31A	http://schemas.xmlsoap.org/ws/2004/10/wsat/Committed
0x31C	http://schemas.xmlsoap.org/ws/2004/10/wsat/Aborted
0x31E	http://schemas.xmlsoap.org/ws/2004/10/wsat/Prepare
0x320	http://schemas.xmlsoap.org/ws/2004/10/wsat/Prepared

Value	Characters
0x322	http://schemas.xmlsoap.org/ws/2004/10/wsat/ReadOnly
0x324	http://schemas.xmlsoap.org/ws/2004/10/wsat/Replay
0x326	http://schemas.xmlsoap.org/ws/2004/10/wsat/fault
0x328	CompletionCoordinatorPortType
0x32A	CompletionParticipantPortType
0x32C	CoordinatorPortType
0x32E	ParticipantPortType
0x330	InconsistentInternalState
0x332	mstx
0x334	Enlistment
0x336	protocol
0x338	LocalTransactionId
0x33A	IsolationLevel
0x33C	IsolationFlags
0x33E	Description
0x340	Loopback
0x342	RegisterInfo
0x344	ContextId
0x346	TokenId
0x348	AccessDenied
0x34A	InvalidPolicy
0x34C	CoordinatorRegistrationFailed
0x34E	TooManyEnlistments
0x350	Disabled
0x352	ActivityId
0x354	http://schemas.microsoft.com/2004/09/ServiceModel/Diagnostics
0x356	http://docs.oasis-open.org/wss/oasis-wss-kerberos-token-profile-1.1#Kerberosv5APREQSHA1
0x358	http://schemas.xmlsoap.org/ws/2002/12/policy
0x35A	FloodMessage
0x35C	LinkUtility

Value	Characters
0x35E	Hops
0x360	http://schemas.microsoft.com/net/2006/05/peer/HopCount
0x362	PeerVia
0x364	http://schemas.microsoft.com/net/2006/05/peer
0x366	PeerFlooder
0x368	PeerTo
0x36A	http://schemas.microsoft.com/ws/2005/05/routing
0x36C	PacketRoutable
0x36E	http://schemas.microsoft.com/ws/2005/05/addressing/none
0x370	http://schemas.microsoft.com/ws/2005/05/envelope/none
0x372	http://www.w3.org/2001/XMLSchema-instance
0x374	http://www.w3.org/2001/XMLSchema
0x376	nil
0x378	type
0x37A	char
0x37C	boolean
0x37E	byte
0x380	unsignedByte
0x382	short
0x384	unsignedShort
0x386	int
0x388	unsignedInt
0x38A	long
0x38C	unsignedLong
0x38E	float
0x390	double
0x392	decimal
0x394	dateTime
0x396	string
0x398	base64Binary

Value	Characters
0x39A	anyType
0x39C	duration
0x39E	guid
0x3A0	anyURI
0x3A2	QName
0x3A4	time
0x3A6	date
0x3A8	hexBinary
0x3AA	gYearMonth
0x3AC	gYear
0x3AE	gMonthDay
0x3B0	gDay
0x3B2	gMonth
0x3B4	integer
0x3B6	positiveInteger
0x3B8	negativeInteger
0x3BA	nonPositiveInteger
0x3BC	nonNegativeInteger
0x3BE	normalizedString
0x3C0	ConnectionLimitReached
0x3C2	http://schemas.xmlsoap.org/soap/envelope/
0x3C4	actor
0x3C6	faultcode
0x3C8	faultstring
0x3CA	faultactor
0x3CC	detail

3 Structure Examples

Following is an example of how to encode a SOAP document in the SOAP data structure format by using the **strings** specified in section 2. White space (such as spaces, tab characters, and carriage returns) improves readability, but is not part of the encoded version of the document.

```
<s:Envelope xmlns:a="http://www.w3.org/2005/08/addressing"
            xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action s:mustUnderstand="1">action</a:Action>
  </s:Header>
  <s:Body>
    <Inventory>0</Inventory>
  </s:Body>
</s:Envelope>
```

The following table divides the same SOAP document into **records**. Each row in the table represents one record. The first column identifies the text, or record content. The second column identifies the type of SOAP record. The third column shows the record in its encoded form. For information on the structure of each record, see [\[MC-NBFX\]](#).

String to encode	Record type	Encoded bytes (hex)
<s:Envelope	PrefixDictionaryElementS	56 02
xmlns:a="http://www.w3.org/2005/08/addressing"	DictionaryXmlnsAttribute	0B 01 61 06
xmlns:s="http://www.w3.org/2003/05/soap-envelope">	DictionaryXmlnsAttribute	0B 01 73 04
<s:Header>	PrefixDictionaryElementS	56 08
<a:Action	PrefixDictionaryElementA	44 0A
s:mustUnderstand="1">	PrefixDictionaryAttributeS	1E 00 82
action</a:Action>	Chars8TextWithEndElement	99 06 61 63 74 69 6F 6E
</s:Header>	EndElement	01
<s:Body>	PrefixDictionaryElementS	56 0E
<Inventory>	ShortElement	40 09 49 6E 76 65 6E 74 6F 72 79
0</Inventory>	ZeroTextWithEndElement	81
</s:Body>	EndElement	01
</s:Envelope>	EndElement	01

Several of the records contain [DictionaryString](#) entries, as specified in section 2. The bytes that map to DictionaryString entries are highlighted in **bold** in records 1 through 6, and in record 9.

Finally, the following diagram shows the SOAP document as a byte stream.

```
56 02 0B 01 61 06 0B 01 73 04 56 08 44 0A 1E 00
82 99 06 61 63 74 69 6F 6E 01 56 0E 40 09 49 6E
76 65 6E 74 6F 72 79 81 01 01
```

4 Security Considerations

For information on security considerations, see [\[MC-NBFX\]](#) section 1.3.

5 Appendix A: Product Behavior

This document specifies version-specific details in the Microsoft® .NET Framework. The following versions of .NET Framework are available in the following released Microsoft Windows® product or as supplemental software, see **.NET Framework**.

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® .NET Framework 3.0
- Microsoft® .NET Framework 3.5
- Microsoft® .NET Framework 4.0

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

6 Change Tracking

This section identifies changes that were made to the [MC-NBFS] protocol document between the May 2011 and June 2011 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1.2 References	Added explanatory statement regarding the removal of the publishing year from Microsoft Open Specification document references.	N	Content updated.

7 Index

A

[Applicability](#) 6

C

[Change tracking](#) 28

D

[Dictionary](#) 7

F

[Fields - vendor-extensible](#) 6

G

[Glossary](#) 5

I

[Informative references](#) 6

[Introduction](#) 5

L

[Localization](#) 6

N

[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Product behavior](#) 27

R

References

[informative](#) 6

[normative](#) 5

[Relationship to other protocols](#) 6

S

[Security - overview](#) 26

[Structure example - SOAP encoding](#) 24

[Structures](#) 7

T

[Tracking changes](#) 28

V

[Vendor-extensible fields](#) 6

[Versioning](#) 6