

[MS-WMLOG]: Windows Media Log Data Structure

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/03/2007	0.01		MCPP Milestone Longhorn Initial Availability
07/03/2007	1.0	Major	MLonghorn+90
07/20/2007	2.0	Major	Revised technical content; added example topics.
08/10/2007	2.0.1	Editorial	Revised and edited the technical content.
09/28/2007	2.0.2	Editorial	Revised and edited the technical content.
10/23/2007	2.0.3	Editorial	Revised and edited the technical content.
11/30/2007	2.0.4	Editorial	Revised and edited the technical content.
01/25/2008	2.0.5	Editorial	Revised and edited the technical content.
03/14/2008	2.1	Minor	Updated the technical content.
05/16/2008	2.1.1	Editorial	Revised and edited the technical content.
06/20/2008	2.2	Minor	Updated the technical content.
07/25/2008	2.3	Minor	Updated the technical content.
08/29/2008	2.4	Minor	Updated the technical content.
10/24/2008	2.4.1	Editorial	Revised and edited the technical content.
12/05/2008	3.0	Major	Updated and revised the technical content.
01/16/2009	3.1	Minor	Updated the technical content.
02/27/2009	3.1.1	Editorial	Revised and edited the technical content.
04/10/2009	3.2	Minor	Updated the technical content.
05/22/2009	4.0	Major	Updated and revised the technical content.
07/02/2009	4.0.1	Editorial	Revised and edited the technical content.
08/14/2009	4.0.2	Editorial	Revised and edited the technical content.
09/25/2009	4.1	Minor	Updated the technical content.
11/06/2009	4.1.1	Editorial	Revised and edited the technical content.
12/18/2009	4.1.2	Editorial	Revised and edited the technical content.
01/29/2010	4.2	Minor	Updated the technical content.
03/12/2010	4.2.1	Editorial	Revised and edited the technical content.

Date	Revision History	Revision Class	Comments
04/23/2010	4.2.2	Editorial	Revised and edited the technical content.
06/04/2010	4.2.3	Editorial	Revised and edited the technical content.
07/16/2010	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
08/27/2010	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2010	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
01/07/2011	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2011	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
03/25/2011	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
05/06/2011	4.2.3	No change	No changes to the meaning, language, or formatting of the technical content.
06/17/2011	4.3	Minor	Clarified the meaning of the technical content.

Contents

1	Introduction	6
1.1	Glossary	6
1.2	References.....	6
1.2.1	Normative References.....	6
1.2.2	Informative References	7
1.3	Overview	7
1.4	Relationship to Protocols and Other Structures	8
1.5	Applicability Statement.....	8
1.6	Versioning and Localization	8
1.7	Vendor-Extensible Fields.....	8
2	Structures	9
2.1	Log Data Fields.....	9
2.1.1	audiocodec	9
2.1.2	avgbandwidth	10
2.1.3	c-buffercount	10
2.1.4	c-cpu	10
2.1.5	c-dns	11
2.1.6	c-hostexe	11
2.1.7	c-hostexever	11
2.1.8	c-ip	12
2.1.9	c-max-bandwidth	12
2.1.10	c-os	12
2.1.11	c-osversion	13
2.1.12	c-pkts-lost-client	13
2.1.13	c-pkts-lost-cont-net	13
2.1.14	c-pkts-lost-net	14
2.1.15	c-pkts-received	14
2.1.16	c-pkts-recovered-ECC	14
2.1.17	c-pkts-recovered-resent	15
2.1.18	c-playerid	15
2.1.19	c-playerlanguage.....	16
2.1.20	c-playerversion	16
2.1.21	c-quality.....	17
2.1.22	c-rate.....	17
2.1.23	c-resendreqs.....	18
2.1.24	c-starttime	18
2.1.25	c-status.....	18
2.1.25.1	Status Code 200 (No Error).....	19
2.1.25.2	Status Code 210 (Client Successfully Reconnected).....	19
2.1.26	c-totalbuffertime	19
2.1.27	c-channelURL.....	19
2.1.28	c-bytes.....	19
2.1.29	cs-media-name	20
2.1.30	cs-media-role.....	20
2.1.31	cs-Referer	21
2.1.32	cs-url	21
2.1.33	cs-uri-stem	22
2.1.34	cs-User-Agent	22
2.1.35	cs-user-name.....	23

2.1.36	date.....	23
2.1.37	filelength.....	24
2.1.38	filesize	24
2.1.39	protocol.....	24
2.1.40	s-content-path	25
2.1.41	s-cpu-util.....	25
2.1.42	s-dns	25
2.1.43	s-ip.....	26
2.1.44	s-pkts-sent	26
2.1.45	s-proxied.....	26
2.1.46	s-session-id	27
2.1.47	s-totalclients	27
2.1.48	sc-bytes	27
2.1.49	time.....	28
2.1.50	transport	28
2.1.51	videocodec	28
2.1.52	x-duration	29
2.2	Logging Message: W3C Syntax.....	29
2.2.1	Basic Logging Syntax.....	30
2.2.2	Extended Logging Syntax	30
2.3	Logging Messages Sent to Web Servers	30
2.4	Logging Message: XML Schema	32
2.5	Legacy Log	34
2.5.1	Common Definitions	34
2.5.2	Legacy Log in W3C Format	35
2.5.3	Legacy Log in XML Format.....	36
2.5.4	Legacy Log Sent to a Web Server	36
2.6	Streaming Log.....	36
2.6.1	Common Definitions	36
2.6.2	Streaming Log Sent to Windows Media Services	38
2.6.3	Streaming Log Sent to a Web Server	38
2.7	Rendering Log	38
2.7.1	Common Definitions	38
2.7.2	Rendering Log Sent to Windows Media Services	39
2.7.3	Rendering Log Sent to a Web Server	40
2.8	Connect-Time Log.....	40
3	Structure Examples	42
3.1	Legacy Logging Message.....	42
3.2	Defining Custom Namespaces in an XML Log	43
3.3	Example Streaming Log Messages	44
3.4	Example Rendering Log Messages.....	46
3.5	Example Connect-Time Log Message	47
3.6	Example Log Sent to a Web Server	47
3.7	Parsing Windows Media Log Files	48
4	Security Considerations.....	49
5	Appendix A: Product Behavior	50
6	Change Tracking.....	52
7	Index	54

1 Introduction

This specification defines the Windows Media Log Data Structure. The Windows Media Log Data Structure is a syntax for logging messages. The logging messages specify information about how a client received multimedia content from a streaming server. For example, logging messages can specify how many packets were received and how long it took for the client to receive the content.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Advanced Systems Format (ASF)
globally unique identifier (GUID)

The following terms are defined in [\[MS-WMSP\]](#):

content
Internet host name
playlist
session
stream
streaming

The following terms are specific to this document:

client: The entity that has created the logging message, or an entity that receives a logging message from a client. In the latter case, the client is a proxy.

proxy: An entity that can receive logging messages from both a client and a proxy, or from a server that is streaming on behalf of another server.

server: An entity that transfers content to a client through streaming. A server might be able to do streaming on behalf of another server; thus, a server can also be a proxy.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ASF] Microsoft Corporation, "Advanced Systems Format Specification", December 2004, http://download.microsoft.com/download/7/9/0/790fecaa-f64a-4a5e-a430-0bccdab3f1b4/ASF_Specification.doc

If you have any trouble finding [ASF], please check [here](#).

[RFC1945] Berners-Lee, T., Fielding, R., and Frystyk, H., "Hypertext Transfer Protocol -- HTTP/1.0", RFC 1945, May 1996, <http://www.ietf.org/rfc/rfc1945.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2326] Schulzrinne, H., Rao, A., and Lanphier, R., "Real Time Streaming Protocol (RTSP)", RFC 2326, April 1998, <http://www.ietf.org/rfc/rfc2326.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>

[RFC3629] Yergeau, F., "UTF-8, A Transformation Format of ISO 10646", STD 63, RFC 3629, November 2003, <http://www.ietf.org/rfc/rfc3629.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.ietf.org/rfc/rfc3986.txt>

[RFC4234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-MMSP] Microsoft Corporation, "[Microsoft Media Server \(MMS\) Protocol Specification](#)".

[MS-MSB] Microsoft Corporation, "[Media Stream Broadcast \(MSB\) Protocol Specification](#)".

[MS-RTSP] Microsoft Corporation, "[Real-Time Streaming Protocol \(RTSP\) Windows Media Extensions](#)".

[MS-WMSP] Microsoft Corporation, "[Windows Media HTTP Streaming Protocol Specification](#)".

[MSDN-WMMETA] Microsoft Corporation, "Windows Media Metafiles", [http://msdn.microsoft.com/en-us/library/dd564665\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/dd564665(VS.85).aspx)

[MSFT-LOGPARSER] Microsoft Corporation, "Log Parser 2.2", <http://www.microsoft.com/downloads/details.aspx?FamilyID=890cd06b-abf8-4c25-91b2-f8d975cf8c07&displaylang=en>

[W3C-EXLOG] World Wide Web Consortium, "Extended Log File Format", <http://www.w3.org/TR/WD-logfile.html>

1.3 Overview

The Windows Media Log Data Structure is a syntax for logging messages. The logging messages specify information about how a **client** received multimedia **content** from a **streaming server**.

1.4 Relationship to Protocols and Other Structures

The logging messages defined in this specification are used by the [Windows Media HTTP Streaming Protocol](#) and the [Real-Time Streaming Protocol \(RTSP\) Windows Media Extensions](#). When those two protocols are used, the logging messages defined by this specification can be encapsulated in protocol messages specific to the streaming protocol in use. The resulting protocol messages are sent to either Windows® Media Services or to a proxy compatible with the logging message syntax defined in this specification.

It is also possible to send logging messages to an HTTP Web server. This is possible when using the two streaming protocols mentioned earlier and when using two other streaming protocols: [Microsoft Media Server \(MMS\) Protocol](#) and [Media Stream Broadcast \(MSB\) Protocol](#).

1.5 Applicability Statement

The syntax for logging messages defined by this specification is applicable to implementations of the four streaming protocols mentioned in section [1.4](#).

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

Logging messages in XML format are vendor-extensible. Any logging information added by a vendor MUST be encoded using the "client-logging-data" syntax element specified in section [2.4](#).

2 Structures

Section [2.1](#) defines fields that can appear in a logging message. Not all fields appear in all logging messages, however. Section [2.2](#) defines the syntax of World Wide Web Consortium (W3C)-based logging messages, and section [2.4](#) defines the syntax of XML-based logging messages.

Section [2.5](#) defines the legacy logging message type. Section [2.6](#) defines the Streaming Log message type. Section [2.7](#) defines the Rendering Log message type. Section [2.8](#) defines the Connection Log message type.

Note These sections may also contain variants that supersede the definitions in [2.1](#).

The information contained in a logging message is always specific to a particular session. The extent of a session is defined by the streaming protocol used by the server. A Rendering Log message (as specified in section [2.7](#)) can be sent without streaming from a server, and, in that case, a session starts when the playback of the playlist starts and stops when the playback of the playlist stops.

Following are some common Augmented Backus-Naur Form (ABNF) constructions, as specified in [\[RFC4234\]](#), that are used throughout this specification. Any ABNF syntax rules that are not defined in [\[RFC4234\]](#) or in this specification may be defined in [\[RFC1945\]](#) or [\[RFC2616\]](#).

```
date-year      = 4DIGIT          ; "19xx" and "20xx" typical
date-month     = 2DIGIT          ; 01 through 12
date-day       = 2DIGIT          ; 01 through 31
time-hour      = 2DIGIT          ; 00 through 24
time-min       = 2DIGIT          ; 00 through 59
time-sec       = 2DIGIT          ; 00 through 59, 60 if leap second

ip_addr        = IPv4address | IPv6address
                ; Defined in Appendix A of RFC3986

ver_major      = 1*2DIGIT
ver_minor      = 1*2DIGIT [ "." 1*4DIGIT "." 1*4DIGIT ]
```

2.1 Log Data Fields

2.1.1 audiocodec

This field **SHOULD** specify a list of audio codecs used to decode the audio **streams** accessed by the client. Each codec **MUST** be listed only once regardless of the number of streams decoded by that codec.

The value for **audiocodec** **MUST NOT** exceed 256 characters in total length. If the codec name is not available, the field **MUST** be set to "-".

The syntax of the **audiocodec** field is defined as follows.

```
codec-name= 1*255VCHAR
audiocodec= "-" | ( codec-name *( ";" codec-name ) )
```

Example:

2.1.2 avgbandwidth

This field MUST specify the average bandwidth, in bits per second, at which the client received content from the server (which may be a **proxy**), as measured by the client from the start of the current session. This is only applicable during periods in which the server is streaming the content. Depending on the streaming protocol used, it might be possible for the session to be in a "paused" state in which streaming is suspended. The value for **avgbandwidth** does not account for the average bandwidth during such periods in which streaming is suspended.

If the notion of an average bandwidth is not applicable, for example, because the client did not receive any content from the server, then the field MUST be set to "-".

If the numerical value is specified, it MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **avgbandwidth** field is defined as follows.

```
avgbandwidth= "-" | 1*10DIGIT
```

Example:

```
102585
```

2.1.3 c-buffercount

This field MUST specify the number of times the client buffered while playing the content, counted from when the client most recently started streaming the content.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-buffercount** field is defined as follows.

```
c-buffercount= 1*10DIGIT
```

Example:

```
1
```

2.1.4 c-cpu

This field MUST specify the type of CPU used by the client computer.

The syntax of the **c-cpu** field is defined as follows.

```
c-cpu= 1*64VCHAR
```

Example:

```
Pentium
```

2.1.5 c-dns

This field SHOULD be set to "-". The field MAY specify the **Internet host name** of the client sending the log. [<1>](#)

The syntax of the **c-dns** field is defined as follows.

```
c-dns= "-"  
      | reg-name ;
```

as defined in [\[RFC3986\]](#)

Example:

```
wmt.test.com
```

2.1.6 c-hostexe

This field specifies the file name of the host application executed on the client. This field MUST NOT refer to a .dll, .ocx, or other nonexecutable file.

The syntax of the **c-hostexe** field is defined as follows.

```
c-hostexe= *255VCHAR
```

Example:

```
wmplayer.exe
```

2.1.7 c-hostexever

This field MUST specify the version number of the host application running on the client.

The syntax of the **c-hostexever** field is defined as follows.

```
c-hostexever= ver_major "." ver_minor
```

Example:

```
6.2.5.323
```

2.1.8 c-ip

When a client creates a logging message, it SHOULD specify the **c-ip** field as "-" but MAY specify the IP address of the client.

If a proxy is forwarding a logging message on behalf of a client, the **c-ip** field MUST specify the IP address of the client. The proxy MUST replace the value of the **c-ip** field that was specified by the client with the IP address of the client (as known to the proxy).

The syntax of the **c-ip** field is defined as follows.

```
c-ip = "-" | ip_addr
```

Example:

```
157.100.100.100
```

Example:

```
3ffe:2900:d005:f28b:0000:5efe:157.55.145.142
```

2.1.9 c-max-bandwidth

This field MUST be set to "-".

The syntax of the **c-max-bandwidth** field is defined as follows.

```
c-max-bandwidth = "-"
```

Example:

```
-
```

2.1.10 c-os

This field MUST specify the client's operating system. [<2>](#)

The syntax of the **c-os** field is defined as follows.

```
OSname= "Windows_98" | "Windows_ME" | "Windows_NT"  
        | "Windows_2000" | "Windows_XP" | "Windows"  
        | "Windows_Server 2003"  
c-os = OSname | 1*64VCHAR
```

Example:

2.1.11 c-osversion

This field MUST specify the version number of the client's operating system.

The syntax of the **c-osversion** field is defined as follows.

```
c-osversion= ver_major "." ver_minor
```

Example:

```
6.0.0.6000
```

2.1.12 c-pkts-lost-client

This field MUST specify the number of **Advanced Systems Format (ASF)** data packets ([\[ASF\]](#) section 5.2) lost during transmission from server to client and not recovered at the client layer through error correction or at the network layer by using the User Datagram Protocol (UDP) resends, counted from when the client most recently started streaming the content.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-lost-client** field is defined as follows.

```
c-pkts-lost-client= 1*10DIGIT
```

Example:

```
5
```

2.1.13 c-pkts-lost-cont-net

This field MUST specify the largest number of ASF data packets that were lost as a consecutive span during transmission from server to client and counted from when the client most recently started streaming the content.

For example, if data packets numbered 1, 4, and 8 are received, and packets 2, 3, 5, 6 and 7 are lost, then packets 2 and 3 constitute a span of two lost packets, and packets 5, 6 and 7 constitute a span of three lost packets. In this example, the **c-pkts-lost-cont-net** field would be set to 3—the size of the largest span.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-lost-cont-net** field is defined as follows.

```
c-pkts-lost-cont-net= 1*10DIGIT
```

Example:

2

2.1.14 c-pkts-lost-net

This field MUST specify the number of ASF data packets lost on the network layer, counted from when the client most recently started streaming the content. Packets lost at the network layer can be recovered if the client re-creates them by using forward error correction.

The numerical difference between the value of **c-pkts-lost-net** and the value of [c-pkts-lost-client](#) MUST be equal to the value of [c-pkts-recovered-ECC](#).

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-lost-net** field is defined as follows.

```
c-pkts-lost-net= 1*10DIGIT
```

Example:

2

2.1.15 c-pkts-received

This field MUST specify the number of ASF data packets that have been correctly received by the client on the first attempt counted from when the client most recently started streaming the content. (ASF data packets that were received through error correction code (ECC) recovery or UDP resends are not included in the **c-pkts-received** field.)

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-received** field is defined as follows.

```
c-pkts-received= 1*10DIGIT
```

Example:

523

2.1.16 c-pkts-recovered-ECC

This field MUST specify the number of ASF data packets that were lost at the network layer but were subsequently recovered, counted from when the client most recently started streaming the content. The value of this field MUST be equal to the numerical difference between the value of [c-pkts-lost-net](#) and the value of [c-pkts-lost-client](#).

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-recovered-ECC** field is defined as follows.

```
c-pkts-recovered-ECC= 1*10DIGIT
```

Example:

1

2.1.17 c-pkts-recovered-resent

This field MUST specify the number of ASF data packets that were recovered either because they were resent through UDP or because they were received out of order.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-pkts-recovered-resent** field is defined as follows.

```
c-pkts-recovered-resent= 1*10DIGIT
```

Example:

5

2.1.18 c-playerid

This field specifies a unique identifier for the client application that originated the request. The identifier MUST be a **GUID**. The GUID is expressed in registry format and is not enclosed in quotation marks, as shown by the following ABNF syntax.

If the client is configured to remain anonymous (that is, not send private information), the client MUST set the **c-playerid** field as indicated by the ABNF syntax for the `playid_priv` syntax element as shown in the following code example. Otherwise, **c-playerid** MUST use the syntax for `playid_pub` as shown in the following code example. The client MUST choose a value for `playid_pub` randomly, and the same value MUST be used for `playid_pub` in all logging messages created by the client application, regardless of which content is streamed.

Furthermore, multiple instances, or incarnations, of the client application MUST use the same value for the `playid_pub` syntax element. However, if the client application is shared by multiple users, and it is possible to determine a user identity or account name of the user launching the client application, then the value for `playid_pub` SHOULD be different for each user identity or account name. For example, multi-user operating systems typically have separate accounts with a distinct account name for each user, but cellular telephones do not.

If the client uses the `playid_priv` syntax element, the client SHOULD choose the value for the `playid` syntax element randomly; however, the client MUST use the same `playid` value for all logging messages sent for the same session.

The syntax of the **c-playerid** field is defined as follows.

```
playid= 12HEXDIG
```

```
playid_pub = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-"  
              4HEXDIG "-" 12HEXDIG "}"  
playid_priv= "{3300AD50-2C39-46c0-AE0A-" playid "}"  
  
c-playerid= playid_pub / playid_priv
```

Example:

```
{c579d042-cecc-11d1-bb31-00a0c9603954}
```

Example (client is anonymous):

```
{3300AD50-2C39-46c0-AE0A-70b64f321a80}
```

2.1.19 c-playerlanguage

This field MUST specify the language-country code of the client.

The syntax of the **c-playerlanguage** field is defined as follows.

```
c-playerlanguage= Language-Tag  
;
```

see section 2.1 of [\[RFC3066\]](#)

Example:

```
en-US
```

2.1.20 c-playerversion

This field MUST specify the version number of the client.

The syntax of the **c-playerversion** field is defined as follows.

```
c-playerversion = ver_major "." ver_minor
```

Example:

```
7.0.1024
```


2.1.21 c-quality

This field MUST specify the percentage of packets that were received by the client, counted from when the client most recently started streaming the content.

If **cPacketsRendered** represents all packets received by the client including packets recovered by ECC and UDP resend such that:

```
cPacketsRendered = c-pkts-received + c-pkts-recovered-ECC + c-pkts-  
recovered-resent
```

then the value for the **c-quality** field MUST be calculated as follows.

```
[cPacketsRendered / (cPacketsRendered + c-pkts-lost-client)] * 100
```

If the denominator in the above equation evaluates to 0, **c-quality** MUST be specified as 100.

The syntax of the **c-quality** field is defined as follows.

```
c-quality = 1*2DIGIT / "100"
```

Example:

```
89
```

2.1.22 c-rate

This field MUST specify the rate of streaming or playback as a multiplier of the normal streaming or playback rate.

For example, a value of 1 specifies streaming or playback at the normal rate, while a value of -5 indicates rewind at a speed five times faster than real-time, and a value of 5 indicates fast-forward at a rate five times faster than real-time.

For Legacy and Streaming Logs, **c-rate** MUST be the streaming rate. For Rendering logs, **c-rate** MUST be the rendering (playback) rate.

The value of **c-rate** MUST reflect the rate that was in effect at the beginning of the period covered by the logging message because streaming or playback might already have ended by the time the logging message is generated.

The syntax of the **c-rate** field is defined as follows.

```
c-rate= [ "-" ] 1*2DIGIT
```

Example:

2.1.23 c-resendreqs

This field MUST specify the number of requests made by the client to receive lost ASF data packets, counted from when the client most recently started streaming the content. If the client is not using UDP resend, the value of this field MUST be "-".

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-resendreqs** field is defined as follows.

```
c-resendreqs= "-" / 1*10DIGIT
```

Example:

5

2.1.24 c-starttime

This field MUST specify the time offset, in seconds, in the content from which the client started to render content. This represents the presentation time of the ASF data packets that the client began rendering. For live broadcasts, the client MUST set this field to zero.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-starttime** field is defined as follows.

```
c-starttime= 1*10DIGIT
```

Example:

39

2.1.25 c-status

This field MUST specify a numerical code that indicates the status of the client that creates the logging message.

The syntax of the **c-status** field is defined as follows:

```
c-status= "200" / "210"
```

Example:

200

2.1.25.1 Status Code 200 (No Error)

This code indicates that the client successfully streamed and submitted the log.

2.1.25.2 Status Code 210 (Client Successfully Reconnected)

This code indicates that the client disconnected and then reconnected to the server. [<3>](#)

2.1.26 c-totalbuffertime

This field MUST specify the total time, in seconds, that the client spent buffering the ASF data packets in the content, counted from when the client most recently started streaming the content. If the client buffers the content more than once before a log is generated, **c-totalbuffertime** MUST be equal to the total amount of time that the client spent buffering the ASF data packets.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-totalbuffertime** field is defined as follows.

```
c-totalbuffertime= 1*10DIGIT
```

Example:

```
20
```

2.1.27 c-channelURL

This field MUST specify the URL to the multicast station (.nsc) file (for more information, see [\[MS-MSB\]](#)) if such a file was used by the client. Whenever an .nsc file is used, this field MUST be specified, even if the MSB Protocol was not used to stream content.

The syntax of the **c-channelURL** field is defined as follows.

```
c-channelURL  = "-"  
                / URI-reference ;
```

as defined in section 4.1 of [\[RFC3986\]](#).

Example:

```
http://server/channel.nsc
```

2.1.28 c-bytes

This field MUST specify the number of bytes received by the client from the server, counted from when the client most recently started streaming the content.

The value for the **c-bytes** field MUST NOT include TCP/IP or other overhead added by the network stack. Higher-level protocols such as HTTP [\[RFC2616\]](#), RTSP [\[RFC2326\]](#), and the MMS Protocol [\[MS-](#)

[MMSP](#)], can each introduce differing amounts of overhead, resulting in different values for the same content.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **c-bytes** field is defined as follows.

```
c-bytes= 1*10DIGIT
```

Example:

```
28000
```

2.1.29 cs-media-name

The purpose of this field is to specify the file name of the content or server-side **playlist** entry that was streamed or played by the client. For Legacy and Streaming Logs, the value of this field MUST be the content or server-side playlist entry that was streamed. For Rendering Logs, it MUST be the content or server-side playlist entry that was rendered (played).

If the server provided a Content Description, (see, for example, the [Windows Media HTTP Streaming Protocol](#)), and the Content Description contains an entry named WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_URL, the value of the **cs-media-name** field MUST be equal to the value of the WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_URL entry.

Otherwise, if the client is using an Active Stream Redirector (.asx) file (for more information, see [\[MSDN-WMMETA\]](#)), and the file specifies a logging parameter called "cs-media-name", then the value of the **cs-media-name** field in the logging message MUST be equal to the value of the "cs-media-name" logging parameter in the .asx file. See section [3.2](#) for an example of how this parameter is specified in an .asx file.

If none of the preceding applies, **cs-media-name** MUST be specified as "-".

The syntax of the **cs-media-name** field is defined as follows.

```
cs-media-name= *VCHAR
```

Examples:

```
C:\wmpub\wmroot\MyAd2.asf
```

2.1.30 cs-media-role

The purpose of this field is to specify a value that can be associated with a server-side playlist entry to signify the role of the playlist entry. For Legacy and Streaming Logs, the value of this field MUST be the role of the server-side playlist entry that was streamed. For Rendering Logs, it MUST be the role of the server-side playlist entry that was rendered (played).

If the server provided a Content Description (see, for example, the [Windows Media HTTP Streaming Protocol](#)), and the Content Description contains an entry named

WMS_CONTENT_DESCRIPTION_ROLE, the value of the **cs-media-role** field MUST be equal to the value of the WMS_CONTENT_DESCRIPTION_ROLE entry.

Otherwise, if the client is using an Active Stream Redirector (.asx) file (for more information, see [\[MSDN-WMMETA\]](#)), and the file specifies a logging parameter called "cs-media-role", the value of the **cs-media-role** field in the logging message MUST be equal to the value of the "cs-media-role" logging parameter in the .asx file. See section [3.2](#) for an example of how this parameter is specified in an .asx file.

If none of the preceding applies, the **cs-media-role** MUST be specified as "-".

The syntax of the **cs-media-role** field is defined as follows.

```
cs-media-role= *VCHAR
```

Example:

```
ADVERTISEMENT
```

2.1.31 cs-Referer

This field SHOULD specify the URL to the Web page that the client software application is embedded within, except if the client software application was not embedded in a Web page. If the client software application is not embedded in a Web page, but an .asx file (for more information, see [\[MSDN-WMMETA\]](#)) was obtained from a Web page, this field SHOULD be set to the URL to that Web page.

If none of the preceding applies, this field MUST be set to "-".

The syntax of the **cs-Referer** field is defined as follows.

```
cs-Referer= "-"  
           / URI-reference ; as defined in section 4.1 of [RFC3986]
```

Examples:

```
http://www.adventure-works.com/default.htm
```

2.1.32 cs-url

This field MUST specify the URL for the streaming content originally requested by the client.

Note that the value of this field can be different from the URL actually used if the server redirected the client to a different URL, or if the client decided to use a streaming protocol that is different from the one indicated by the URL scheme of the original URL.

When the [MSB Protocol](#) is used, the "asfm" MUST be used as the URL scheme in the **cs-url** field.

The syntax of the **cs-url** field is defined as follows.

`cs-url= URI-reference; as defined in section 4.1 of [RFC3986].`

Example 1:

`mms://www.adventure-works.com/some/content.asf`

Example 2:

`asfm://239.1.2.3:9000`

2.1.33 cs-uri-stem

This field **MUST** specify the URL actually used by the client. Any query strings **MUST** be excluded from the URL. (This means that the value of the **cs-uri-stem** field is equal to the URL actually used by the client, truncated at the first "?" character.)

Note that the value of this field can be different from the URL originally requested by the client if the server redirected the client to a different URL, or if the client decided to use a streaming protocol that is different from the one indicated by the URL scheme of the original URL.

When the [Media Stream Broadcast \(MSB\) Protocol](#) is used (for more information, see [MS-MSB]), the "asfm" **MUST** be used as the URL scheme in the **cs-uri-stem** field.

The syntax of the **cs-uri-stem** field is defined as follows.

`cs-uri-stem= URI-reference; as defined in section 4.1 of [RFC3986].`

Example:

`rtsp://server/test/sample.asf`

2.1.34 cs-User-Agent

The purpose of this field is to specify information regarding the client application that is sending the logging message.

The **cs-User-Agent** field **SHOULD** be set to the same value that Windows® Internet Explorer® specifies on the User-Agent HTTP protocol header. The field **MAY** be set differently as long as it adheres to the ABNF syntax as shown in the following code example.

If a logging message is forwarded by a proxy, the **cs-User-Agent** field **MUST** begin with the string "_via_". The original value specified by the client (which may be another proxy) on the **cs-User-Agent** field **SHOULD** be discarded. The proxy **SHOULD** include a product token on the **cs-User-Agent** field that specifies the brand and version of the proxy.

The syntax of the **cs-User-Agent** field is defined as follows.

```
cs-User-Agent= [ "_via_HTTP/1.0_" ]
               1*( product; [RFC2616] section 3.8
```

```
| comment ); [RFC2616] section 2.2
```

Example 1: media player embedded in Internet Explorer 6 on Windows® XP operating system Service Pack 2 (SP2):

```
Mozilla/4.0_(compatible;_MSIE_6.0;_Windows_NT_5.1;_SV1)
```

Example 2: application based on Windows Media Format 9 Series SDK:

```
Application/2.3 (WMFSDK/9.0.1234)
```

Example 3: proxy:

```
_via_HTTP/1.0_WMCacheProxy/9.00.00.1234
```

2.1.35 cs-user-name

This field **MUST** be set to "-".

The syntax of the **cs-user-name** field is defined as follows.

```
cs-user-name= "-"
```

Example:

```
-
```

2.1.36 date

This field **MUST** specify the current date on the client when the log message is created. The time **MUST** be specified in UTC.

The syntax of the **date** field is defined as follows.

```
date= date-year "-" date-month "-" date-day
```

Example:

```
1997-10-09
```

2.1.37 filelength

This field MUST specify the length of the ASF file, in seconds. For a live broadcast stream, the value for **filelength** is undefined and MUST be set to zero.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **filelength** field is defined as follows.

```
filelength= 1*10DIGIT
```

Example:

```
60
```

2.1.38 filesize

This field MUST specify the size of the ASF file, in bytes. For a live broadcast stream, the value for the **filesize** field is undefined and MUST be set to zero.

The value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **filesize** field is defined as follows.

```
filesize= 1*10DIGIT
```

Example:

```
86000
```

2.1.39 protocol

This field MUST specify the protocol used to stream content to the client.

If the [Windows Media HTTP Streaming Media Protocol](#) was used, the value of the **protocol** field MUST be "http".

If the [RTSP Windows Media Extensions](#) was used, the value of the **protocol** field MUST be "rtsp".

If the [MSB Protocol](#) was used, the value of the **protocol** field MUST be "asfm".

Note The value for **protocol** can be different from the URL moniker used in the stream request.

The syntax of the **protocol** field is defined as follows.

```
protocol= "http" / "rtsp" / "asfm"
```

Example:

http

2.1.40 s-content-path

This field MUST be set to "-".

The syntax of the **s-content-path** field is defined as follows.

```
s-content-path = "-"
```

Example:

-

2.1.41 s-cpu-util

When a client creates a logging message, it MUST specify the **s-cpu-util** field as "-".

If a proxy is forwarding the logging message on behalf of a client (which may be another proxy), the proxy MUST replace the value of the **s-cpu-util** field that was specified by the client with the proxy's current CPU load, in percentage, at the time of forwarding the logging message. If the proxy uses symmetric multiprocessing, the CPU load value MUST be calculated as the average for all processors.

When a numerical value is specified, the value MUST be an integer in the range from 0 through 100.

The syntax of the **s-cpu-util** field is defined as follows.

```
s-cpu-util = "-" | 1*2DIGIT | "100"
```

Example:

40

2.1.42 s-dns

This field SHOULD specify the Internet host name of the proxy if a proxy is forwarding the logging message on behalf of a client (which may be another proxy). The proxy MUST replace the value of the **s-dns** field that was specified by the client with its own Internet host name or with "-" if the Internet host name cannot be determined.

When a client creates a logging message, it SHOULD specify the **s-dns** field as "-" but MAY specify the Internet host name of the server that the client streamed the content from.

The syntax of the **s-dns** field is defined as follows.

```
s-dns= "-"
```

| reg-name ; as defined in [RFC3986].

Example:

wmt.adventure-works.com

2.1.43 s-ip

For Legacy and Streaming Logs, this field **MUST** specify the IP address of the server that the client streamed the content from.

For Rendering Logs, the field **MUST** specify the IP address of the proxy if a proxy is forwarding the logging message on behalf of a client. The proxy **MUST** replace the value of the **s-ip** field that was specified by the client (which may be another proxy) with the IP address used by the proxy when forwarding the Rendering Log to the server (which may be another proxy).

When a client creates a rendering log, it **SHOULD** specify the **s-ip** field as "-" but can specify the IP address of the server that the client streamed the content from.

The syntax of the **s-ip** field is defined as follows.

s-ip = "-" | ip_addr

Example:

155.12.1.234

2.1.44 s-pkts-sent

This field **MUST** be set to "-".

The syntax of the **s-pkts-sent** field is defined as follows.

s-pkts-sent= "-"

Example:

-

2.1.45 s-proxied

This field **MUST** be set to "1" in a logging message that is being forwarded by a proxy. The client that creates the logging message **MUST** set the field to "0", and the proxy **MUST** change the value to "1" when it forwards the logging message.

The syntax of the **s-proxied** field is defined as follows.

```
s-proxied= "0" / "1"
```

Example:

```
1
```

2.1.46 s-session-id

This field MUST be set to "-".

The syntax of the **s-session-id** field is defined as follows.

```
s-session-id= "-"
```

Example:

```
-
```

2.1.47 s-totalclients

When a client creates a logging message, it MUST specify the **s-totalclients** field as "-".

If a proxy is forwarding the logging message on behalf of a client (which may be another proxy), the proxy MUST replace the value of the **s-totalclients** field that was specified by the client with the total number of clients connected to the proxy server (for all target servers combined).

When a numerical value is specified, the value MUST be an integer in the range from 0 through 4,294,967,295.

The syntax of the **s-totalclients** field is defined as follows.

```
s-totalclients = "-" | 1*10DIGIT
```

Example:

```
201
```

2.1.48 sc-bytes

This field MUST be set to "-".

The syntax of the **sc-bytes** field is defined as follows.

```
sc-bytes= "-"
```

Example:

-

2.1.49 time

This field **MUST** specify the current time on the client when the log message is created. The time **MUST** be specified in UTC.

The syntax of the **time** field is defined as follows.

```
time= time-hour ":" time-min ":" time-sec
```

Example:

```
15:30:30
```

2.1.50 transport

This field **MUST** specify the transport protocol used to receive the ASF data packets.

The syntax of the **transport** field is defined as follows.

```
transport= "UDP" | "TCP"
```

Example:

```
UDP
```

2.1.51 videocodec

This field **SHOULD** specify a list of video codecs that are used to decode the video streams accessed by the client. Each codec **MUST** be listed only once, regardless of the number of streams decoded by that codec.

The value for **videocodec** **MUST NOT** exceed 256 characters in total length. If the codec name is not available, the field **MUST** be set to "-".

The syntax of the **videocodec** field is defined as follows.

```
codec-name= 1*255VCHAR  
videocodec= "-" | ( codec-name *( ";" codec-name ) )
```

Example:

```
Microsoft_MPEG-4_Video_Codec_V2
```

2.1.52 x-duration

For Legacy and Rendering Log messages, this field **MUST** specify how much of the content has been rendered (played) to the end user, specified in seconds. Time spent buffering data **MUST NOT** be included in this value.

Playback at non-normal play speed does not affect the amount of content rendered, when expressed in time units. For example, if the client was rewinding the content, the **x-duration** value can be computed as the absolute value of the difference between the starting presentation time and ending presentation time.

For Streaming Log messages, the **x-duration** field **MUST** specify the time it took to receive the content, in seconds.

Fractional time amounts **MUST** be rounded to the nearest larger integer value.

The value **MUST** be an integer in the range from 0 through 4,294,967,295.

The syntax of the **x-duration** field is defined as follows.

```
x-duration= 1*10DIGIT
```

Example:

31

2.2 Logging Message: W3C Syntax

A W3C format logging message consists of the values of various fields, each value separated from the next by a single space character. Logging messages that adhere to this syntax are said to use the W3C format because the syntax is conformant with the syntax for logging entries in the Extended Log File Format (for more information, see [\[W3C-EXLOG\]](#)), which is defined by W3C.

Section [2.2.1](#) specifies the W3C format syntax used in most logging messages. Section [2.2.2](#) specifies the W3C format syntax used in certain Rendering Log messages.

The sections mentioned earlier define the ordering of the fields in the W3C format syntax but not how the values of the fields are assigned. The rules governing the values of the individual fields depend on the logging message in which the W3C format syntax is used. For example, the [s-ip](#) field is used as defined in section [2.1.43](#) for some logging messages, while other logging messages provide an alternate definition of the **s-ip** field.

All W3C format syntax **MUST** use the UTF-8 character set as specified in [\[RFC3629\]](#). In any fields that specify a URL, such as [cs-url](#), the URL **MUST** be encoded using percent-encoding, as specified in [\[RFC3986\]](#) section 2.1.

A single dash character (which is represented by U+002D and by "-" in ABNF syntax) **MUST** be used to indicate that the value is empty—that is, it is either not available or not applicable.

All spaces embedded within a field value **MUST** be replaced by an underscore character (which is represented by U+005F and by "_" in ABNF syntax). For example, "MPEG Layer-3" would be transformed into "MPEG_Layer-3" in a W3C-format logging message.

Note Transformations defined in this section are not necessarily reversible. Methods for parsing, analyzing, or extracting information from logging messages are implementation-specific and are outside the scope of this specification.

2.2.1 Basic Logging Syntax

Most logging messages contain logging information in W3C format, adhering to the syntax specified as follows. The logging information consists of either 44 or 47 fields.

```
log_data44 = c-ip SP date SP time SP c-dns SP cs-uri-stem SP c-starttime SP
            x-duration SP c-rate SP c-status SP c-playerid SP
            c-playerversion SP c-playerlanguage SP cs-User-Agent SP
            cs-Referer SP c-hostexe SP c-hostexever SP c-os SP c-osversion SP
            c-cpu SP filelength SP filesize SP avgbandwidth SP protocol SP
            transport SP audiocodec SP videocodec SP c-channelURL SP sc-bytes SP
            c-bytes SP s-pkts-sent SP c-pkts-received SP c-pkts-lost-client SP
            c-pkts-lost-net SP c-pkts-lost-cont-net SP c-resendreqs SP
            c-pkts-recovered-ECC SP c-pkts-recovered-resent SP c-buffercount SP
            c-totalbuffertime SP c-quality SP s-ip SP s-dns SP
            s-totalclients SP s-cpu-util
            [ SP cs-url SP cs-media-name SP cs-media-role ]
```

2.2.2 Extended Logging Syntax

Certain types of "rendering" log messages (section 2.7) contain logging information in the W3C format defined as follows. This logging information consists of 52 fields.

```
log_data52 = c-ip SP date SP time SP c-dns SP cs-uri-stem SP c-starttime SP
            x-duration SP c-rate SP c-status SP c-playerid SP
            c-playerversion SP c-playerlanguage SP cs-User-Agent SP
            cs-Referer SP c-hostexe SP c-hostexever SP c-os SP c-osversion SP
            c-cpu SP filelength SP filesize SP avgbandwidth SP protocol SP
            transport SP audiocodec SP videocodec SP c-channelURL SP sc-bytes SP
            c-bytes SP s-pkts-sent SP c-pkts-received SP c-pkts-lost-client SP
            c-pkts-lost-net SP c-pkts-lost-cont-net SP c-resendreqs SP
            c-pkts-recovered-ECC SP c-pkts-recovered-resent SP c-buffercount SP
            c-totalbuffertime SP c-quality SP s-ip SP s-dns SP
            s-totalclients SP s-cpu-util SP cs-user-name SP s-session-id SP
            s-content-path SP cs-url SP cs-media-name SP c-max-bandwidth SP
            cs-media-role SP s-proxied
```

2.3 Logging Messages Sent to Web Servers

Most of the logging messages defined in this specification can be sent to a HTTP Web server. The URL for the HTTP Web server for which logging messages are submitted can be specified in an .asx file (for more information, see [\[MSDN-WMMETA\]](#)). Some of the compatible streaming protocols (listed in section 1.4) can also specify the HTTP Web server URL through mechanisms that are specific to the streaming protocol. The syntax for the logging URL is defined as follows.

```
log-URL = Request-URI
```

The resource that is identified by log-URL MUST be capable of accepting and responding to the HTTP GET and POST request methods described in this section; however, the methods for doing so are implementation-specific.

Prior to sending a logging message to a Web server, a client SHOULD send an HTTP GET request to the specified Web server URL to validate the URL. The logging validation request MUST adhere to the following ABNF syntax.

```
web-server-validate = "GET" SP log-URL SP HTTP-Version CRLF
                     *( VCHAR /CRLF )
```

The Web server's response MUST adhere to the following ABNF syntax.

```
web-server-validate-response = HTTP-Version "200 OK" CRLF
                              *( VCHAR / CRLF ) "<body><h1>"
                              ( "NetShow ISAPI Log Dll" /
                                ( "WMS ISAPI Log Dll/"
                                  1*4DIGIT "." 1*4DIGIT "." 1*4DIGIT "." 1*4DIGIT ) )
                              *( VCHAR / CRLF ) "</h1>" *( VCHAR / CRLF ) </body>" *( VCHAR / CRLF )
```

The client SHOULD send the logging message to the Web server if the server's response adheres to the syntax for Web-server-validate-response. If the client sent a request to validate the URL, and the server's response does not adhere to the syntax for Web-server-validate-response, this might mean that the URL is invalid. In this case, the client SHOULD NOT send the logging message.

When sending the logging message, the client MUST include the logging message in the body of a HTTP POST request.

All logging message requests that are sent to a Web server MUST adhere to the following ABNF syntax:

```
web-server-request = "POST" SP log-URL SP HTTP-Version CRLF
                    *( VCHAR / CRLF )
                    web-server-log
```

The logging message sent in the Web-server-request message body MUST adhere to the following ABNF syntax.

```
web-server-log = "MX_STATS_LogLine:" SP TAB
                 log_data44; defined in section 2.2.1
```

All HTTP GET and POST requests sent by the client or Web server must be syntactically correct as per [\[RFC1945\]](#) or [\[RFC2616\]](#). Any header or content element not explicitly represented in one of the preceding ABNF syntax examples MUST be ignored by the recipient.

For an example of logging URL validation and the subsequent transmission of a logging message to a Web server, see section [3.6](#).

2.4 Logging Message: XML Schema

Logging messages can be represented in XML. This section defines the schema used by all logging messages for which an XML representation has been defined with the exception of the [Connect-Time Log](#). The XML scheme for the Connect-Time Log is defined in section [2.8](#).

The XML-format log embeds W3C-format logging information inside the "Summary" XML tag. Individual logging fields are also represented using their own XML tags.

If the entity that generates the XML-format logging message (that is, the client) has access to a Content Description, each name/value pair in the Content Description SHOULD be encoded as shown by the "contentdescription" syntax element in the ABNF syntax as shown in the following code example.

The Content Description is a data structure that is provided by Windows Media Services. If no Content Description is available to the client, the "contentdescription" syntax element MUST NOT be included in the XML-format logging message.

If the entity that generates the XML-format logging message (that is, the client) submits additional or custom logging information, it SHOULD be encoded as shown by the "client-logging-data" syntax element in the following ABNF syntax. For an example illustrating submission of custom logging information, see section [3.2](#).

If no additional logging information is available, the "client-logging-data" syntax element MUST NOT be included in the XML-format logging message.

The XML-format logging syntax is defined using ABNF as shown in the following code example. Although not explicitly shown by the syntax, linear white space, including CR LF sequences, is allowed on each side of XML tags.

```
xml-tag = 1*ALPHA
cd-name = xml-tag
cd-value = xml-tag
cd-name-value-pair = "<" cd-name ">"
cd-value
    "</" cd-name ">"

contentdescription = "<ContentDescription>"
    *cd-name-value-pair
    "</ContentDescription>"

client-logging-data = "<" xml-tag ">"
    *cdl-name-value-pair
    "</" xml-tag ">"

xml-log = "<XML>"
    "<Summary>" summary-log "</Summary>"
    "<c-ip>" "0.0.0.0" "</c-ip>"
    "<date>" date "</date>"
    "<time>" time "</time>"
```



```

"<c-dns>" c-dns "</c-dns>"
"<cs-uri-stem>" cs-uri-stem "</cs-uri-stem>"
"<c-starttime>" c-starttime "</c-starttime>"
"<x-duration>" x-duration "</x-duration>"
"<c-rate>" c-rate "</c-rate>"
"<c-status>" c-status "</c-status>"
"<c-playerid>" c-playerid "<c-playerid>"
"<c-playerversion>" c-playerversion "</c-playerversion>"
"<c-playerlanguage>" c-playerlanguage "</c-playerlanguage>"
"<cs-User-Agent>" cs-User-Agent "</cs-User-Agent>"
"<cs-Referer>" cs-Referer "<cs-Referer>"
"<c-hostexe>" c-hostexe "</c-hostexe>"
"<c-hostexever>" c-hostexever "</c-hostexever>"
"<c-os>" c-os "</c-os>"
"<c-osversion>" c-osversion "</c-osversion>"
"<c-cpu>" c-cpu "</c-cpu>"
"<filelength>" filelength "</filelength>"
"<filesize>" filesize "</filesize>"
"<avgbandwidth>" avgbandwidth "</avgbandwidth>"
"<protocol>" protocol "</protocol>"
"<transport>" transport "</transport>"
"<audiocodec>" audiocodec "</audiocodec>"
"<videocodec>" videocodec "</videocodec>"
"<c-channelURL>" c-channelURL "</c-channelURL>"
"<sc-bytes>" sc-bytes "</sc-bytes>"
"<c-bytes>" c-bytes "</c-bytes>"
"<s-pkts-sent>" s-pkts-sent "</s-pkts-sent>"
"<c-pkts-received>" c-pkts-received "</c-pkts-received>"
"<c-pkts-lost-client>" c-pkts-lost-client "</c-pkts-lost-client>"
"<c-pkts-lost-net>" c-pkts-lost-net "</c-pkts-lost-net>"
"<c-pkts-lost-cont-net>" c-pkts-lost-cont-net "</c-pkts-lost-cont-net>"
"<c-resendsreqs>" c-resendsreqs "</c-resendsreqs>"
"<c-pkts-recovered-ECC>" c-pkts-recovered-ECC "</c-pkts-recovered-ECC>"
"<c-pkts-recovered-resent>" c-pkts-recovered-resent "</c-pkts-recovered-resent>"
"<c-buffercount>" c-buffercount "</c-buffercount>"
"<c-totalbuffertime>" c-totalbuffertime "</c-totalbuffertime>"
"<c-quality>" c-quality "</c-quality>"
"<s-ip>" "-" "</s-ip>"
"<s-dns>" "-" "</s-dns>"
"<s-totalclients>" "-" "</s-totalclients>"
"<s-cpu-util>" "-" "</s-cpu-util>"
"<cs-url>" cs-url "</cs-url>"
[ contentdescription ]
*client-logging-data
"</XML>"

```

The syntax only defines the ordering of the fields and the XML tag assigned to each field; it does not define how the values of the fields are assigned. The rules governing the values of the individual fields depend on the logging message in which the XML-format syntax is used.

The XML-format logging syntax MUST use the UTF-8 character set, as specified in [RFC3629](#). In any fields that specify a URL, such as cs-url, the URL MUST be encoded using percent-encoding, as specified in [RFC3986](#) section 2.1.

A single dash character (which is represented by U+002D and by "-" in ABNF syntax) MUST be used to indicate that the value is empty—that is, it is either not available or not applicable.

All spaces embedded within a field value MUST be replaced by an underscore character (which is represented by U+005F and by "_" in ABNF syntax). For example, "MPEG Layer-3" would be transformed into "MPEG_Layer-3" in a W3C-format logging message.

2.5 Legacy Log

The Legacy Log is also called a combination log because it contains both rendering and streaming information. The Legacy Log can be either in W3C format or XML format. A Legacy Log can be sent either to Windows Media Services or to a Web server.

2.5.1 Common Definitions

The following ABNF syntax rules applies to all variants of the Legacy Log. [<4>](#)

```
s-cpu-util      = "-"
c-ip            = "0.0.0.0"
s-dns          = "-"
```

The values of the following fields MUST be assigned as defined in section [2.1](#):

- **audiocodec**
- **avgbandwidth**
- **c-buffercount**
- **c-channelURL**
- **c-cpu**
- **c-dns**
- **c-hostexe**
- **c-hostexever**
- **c-os**
- **c-osversion**
- **c-pkts-lost-client**
- **c-pkts-lost-cont-net**
- **c-pkts-lost-net**
- **c-pkts-recovered-ECC**
- **c-pkts-recovered-resent**
- **c-playerid**
- **c-playerlanguage**
- **c-playerversion**
- **c-quality**

- **c-rate**
- **c-resendreqs**
- **c-starttime**
- **c-status**
- **c-totalbuffertime**
- **cs-Referer**
- **cs-media-name**
- **cs-uri-stem**
- **cs-url**
- **cs-User-Agent**
- **date**
- **filelength**
- **filesize**
- **protocol**
- **cs-media-role**
- **s-pkts-sent**
- **s-totalclients**
- **sc-bytes**
- **time**
- **transport**
- **videocodec**
- **x-duration**

The [Legacy Log](#) SHOULD include the optional fields **cs-url**, **cs-media-name**, and **cs-media-role**.<5>

2.5.2 Legacy Log in W3C Format

The ABNF syntax for a [Legacy Log](#) in W3C format that is sent to Windows Media Services is defined as follows.

```

legacy-log-W3C      = log_data44           ; defined in section 2.2.1
s-ip                 = "-"

```

2.5.3 Legacy Log in XML Format

The ABNF syntax for a [Legacy Log](#) in XML format that is sent to Microsoft Windows® Media Services is defined as follows. [<6>](#)

```
legacy-log-XML      = xml-log          ; defined in section 2.4
summary-log         = log_data44       ; defined in section 2.2.1
s-ip                 = "-"
```

2.5.4 Legacy Log Sent to a Web Server

The ABNF syntax for a [Legacy Log](#) that is submitted to a Web server is defined as follows.

```
legacy-web-server-log = web-server-log ; defined in section 2.3
```

The value of the **s-ip** field MUST be assigned as defined in section [2.1.43](#).

2.6 Streaming Log

The Streaming Log specifies how the client received streaming data but not how the client rendered the data. A Streaming Log can be sent either to Windows® Media Services or to a Web server.

2.6.1 Common Definitions

The following ABNF syntax rules apply to all variants of the [Streaming Log](#).

```
audiocodec          = "-"
c-ip                  = "0.0.0.0"
s-cpu-util           = "-"
s-dns                 = "-"
videocodec           = "-"
```

The values of the following fields MUST be assigned as defined in section [2.1](#):

- **avgbandwidth**
- **c-buffercount**
- **c-channelURL**
- **c-cpu**
- **c-dns**
- **c-hostexe**
- **c-hostexeever**
- **c-os**
- **c-osversion**
- **c-pkts-lost-client**

- **c-pkts-lost-cont-net**
- **c-pkts-lost-net**
- **c-pkts-recovered-ECC**
- **c-pkts-recovered-resent**
- **c-playerid**
- **c-playerlanguage**
- **c-playerversion**
- **c-quality**
- **c-rate**
- **c-resendreqs**
- **c-starttime**
- **c-status**
- **c-totalbuffertime**
- **cs-Referer**
- **cs-media-name**
- **cs-uri-stem**
- **cs-url**
- **cs-User-Agent**
- **date**
- **filelength**
- **filesize**
- **protocol**
- **cs-media-role**
- **s-pkts-sent**
- **s-totalclients**
- **sc-bytes**
- **time**
- **transport**
- **x-duration**

The Streaming Log MUST include the optional fields **cs-url**, **cs-media-name**, and **cs-media-role**.

2.6.2 Streaming Log Sent to Windows Media Services

The [Streaming Log](#) sent to Windows® Media Services is in XML format and MUST adhere to the following ABNF syntax. [<7><8>](#)

```
streaming-log      = xml-log          ; defined in section 2.4
summary-log       = log_data44       ; defined in section 2.2.1
s-ip              = "-"
```

2.6.3 Streaming Log Sent to a Web Server

The ABNF syntax for a [Streaming Log](#) that is submitted to a Web server is defined as follows.

```
streaming-web-server-log = web-server-log; defined in section 2.3
```

The value of the **s-ip** field MUST be assigned as specified in section [2.1.43](#).

2.7 Rendering Log

The Rendering Log describes playback of content by a client and is submitted to the upstream origin server (or a configured proxy) when the client ends playback. A Rendering Log can be sent either to Windows® Media Services or to a Web server.

2.7.1 Common Definitions

The following ABNF syntax rules apply to all variants of the [Rendering Log](#):

```
avgbandwidth      = "-"
c-buffercount     = "-"
c-pkts-lost-client = "-"
c-pkts-lost-cont-net = "-"
c-pkts-lost-net    = "-"
c-pkts-received    = "-"
c-pkts-recovered-ECC = "-"
c-pkts-recovered-resent = "-"
c-quality         = "100"
c-resendreqs      = "-"
c-totalbuffertime = "-"
protocol          = "Cache"
transport         = "-"
```

The values of the following fields MUST be assigned as defined in section [2.1](#):

- **audiocodec**
- **c-channelURL**
- **c-cpu**
- **c-hostexe**
- **c-hostexever**
- **c-ip**

- **c-os**
- **c-osversion**
- **c-playerid**
- **c-playerlanguage**
- **c-playerversion**
- **c-rate**
- **c-starttime**
- **c-status**
- **cs-Referer**
- **cs-media-name**
- **cs-uri-stem**
- **cs-url**
- **cs-User-Agent**
- **date**
- **filelength**
- **filesize**
- **s-cpu-util**
- **s-dns**
- **cs-media-role**
- **s-pkts-sent**
- **s-totalclients**
- **sc-bytes**
- **time**
- **videocodec**
- **x-duration**

The Rendering Log MUST include the optional fields **cs-url**, **cs-media-name**, and **cs-media-role**.

2.7.2 Rendering Log Sent to Windows Media Services

The [Rendering Log](#) sent to Windows® Media Services is in XML format and MUST adhere to the following ABNF syntax.

```
rendering-log    = xml-log           ; defined in section 2.4
```

```
summary-log          = log_data52          ; defined in section 2.2.2
```

The values of the following fields **MUST** be assigned as defined in section [2.1](#): **c-max-bandwidth**, **cs-user-name**, **s-content-path**, **s-ip**, **s-proxied**, and **s-session-id**.

2.7.3 Rendering Log Sent to a Web Server

The ABNF syntax for a [Rendering Log](#) that is submitted to a Web server is defined as follows.

```
rendering-web-server-log = web-server-log; defined in section 2.3
```

The value of the **c-ip** field **MUST** be assigned as defined in section [2.1.8](#). The value of the **s-ip** field **MUST** be assigned as defined in section [2.1.43](#).

2.8 Connect-Time Log

The purpose of the Connect-Time Log is to specify some minimal amount of logging information about the client. It can be useful in cases where a client starts to stream some content but is disconnected from the network before it has the opportunity to create a [Streaming Log](#).

If a client sends a Connect-Time Log to the server at the start of the streaming **session**, the Connect-Time Log ensures that the server has received at least this minimal logging information in the case where the client subsequently is disconnected from the network.

Connect-Time Logs are not defined for Web servers. Connect-Time Logs are defined only in XML format, and the ABNF syntax is as follows.

```
connect-time-log = "<XML>"
                  "<Summary>"
                  "</Summary>"
                  "<c-dns>" c-dns "</c-dns>"
                  "<c-ip>" c-ip "</c-ip>"
                  "<c-os>" c-os "</c-os>"
                  "<c-osversion>" c-osversion "</c-osversion>"
                  "<date>" date "</date>"
                  "<time>" time "</time>"
                  "<c-cpu>" c-cpu "</c-cpu>"
                  "<transport>" transport "</transport>"
                  "</XML>"

c-ip              = "0.0.0.0"
```

The values of the following fields **MUST** be assigned as defined in section [2.1](#):

- **c-dns**
- **c-os**
- **c-osversion**
- **date**
- **time**

- **c-cpu**
- **transport**

3 Structure Examples

3.1 Legacy Logging Message

The following is an example of a legacy logging message in W3C format.

```
0.0.0.0 2003-09-27 00:27:24 - http://10.194.20.175/mcast1200K 0 42 1
200 {3300AD50-2C39-46c0-AE0A-B4C904C7848E} 9.0.0.2980 en-US
WMFSDK/9.0.0.2980_WMPlayer/9.0.0.3008 - wmplayer.exe 9.0.0.2980
Windows_XP 5.1.0.2600 Pentium 1801 268885194 1255347 http TCP
Windows_Media_Audio_9 Windows_Media_Video_9 - - 6321233 - 4496 0 0 0 0
0 0 1 0 100 - - - -
```

The following is an example of a legacy logging message in XML format.

```
<XML>
<Summary>0.0.0.0 2003-09-27 00:27:24 - http://10.194.20.175/mcast1200K 0 42 1 200
{3300AD50-2C39-46c0-AE0A-B4C904C7848E} 9.0.0.2980
en-US WMFSDK/9.0.0.2980_WMPlayer/9.0.0.3008 - wmplayer.exe 9.0.0.2980
Windows_XP 5.1.0.2600 Pentium 1801 268885194 1255347
http TCP Windows_Media_Audio_9 Windows_Media_Video_9
- - 6321233 - 4496 0 0 0 0 0 0 1 0 100 - - - -
http://10.194.20.175/mcast1200K?WMBitrate=6000000 30MinTV_1200k_1s_1s_0Q.wmv -
</Summary>
<c-ip>0.0.0.0</c-ip>
<date>2003-09-27</date>
<time>00:27:24</time>
<c-dns>-</c-dns>
<cs-uri-stem>http://10.194.20.175/mcast1200K</cs-uri-stem>
<c-starttime>0</c-starttime>
<x-duration>42</x-duration>
<c-rate>1</c-rate>
<c-status>200</c-status>
<c-playerid>{3300AD50-2C39-46c0-AE0A-B4C904C7848E}</c-playerid>
<c-playerversion>9.0.0.2980</c-playerversion>
<c-playerlanguage>en-US</c-playerlanguage>
<cs-User-Agent>WMFSDK/9.0.0.2980_WMPlayer/9.0.0.3008</cs-User-Agent>
<cs-Referer>-</cs-Referer>
<c-hostexe>wmplayer.exe</c-hostexe>
<c-hostexeversion>9.0.0.2980</c-hostexeversion>
<c-os>Windows_XP</c-os>
<c-osversion>5.1.0.2600</c-osversion>
<c-cpu>Pentium</c-cpu>
<filelength>1801</filelength>
<filesize>268885194</filesize>
<avgbandwidth>1255347</avgbandwidth>
<protocol>http</protocol>
<transport>TCP</transport>
<audiocodec>Windows_Media_Audio_9</audiocodec>
<videocodec>Windows_Media_Video_9</videocodec>
<c-channelURL>-</c-channelURL>
<sc-bytes>-</sc-bytes>
<c-bytes>6321233</c-bytes>
<s-pkts-sent>-</s-pkts-sent>
<c-pkts-received>4496</c-pkts-received>
```

```

<c-pkts-lost-client>0</c-pkts-lost-client>
<c-pkts-lost-net>0</c-pkts-lost-net>
<c-pkts-lost-cont-net>0</c-pkts-lost-cont-net>
<c-resendreqs>0</c-resendreqs>
<c-pkts-recovered-ECC>0</c-pkts-recovered-ECC>
<c-pkts-recovered-resent>0</c-pkts-recovered-resent>
<c-buffercount>1</c-buffercount>
<c-totalbuffertime>0</c-totalbuffertime>
<c-quality>100</c-quality>
<s-ip>-</s-ip>
<s-dns>-</s-dns>
<s-totalclients>-</s-totalclients>
<s-cpu-util>-</s-cpu-util>
<cs-url>http://10.194.20.175/mcast1200K?WMBitrate=6000000</cs-url>
<ContentDescription>
<WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_URL>30MinTV_1200k_1s_1s_0Q.wmv</WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_URL>
<WMS_CONTENT_DESCRIPTION_COPIED_METADATA_FROM_PLAYLIST_FILE>1</WMS_CONTENT_DESCRIPTION_COPIED_METADATA_FROM_PLAYLIST_FILE>
<WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_DURATION>1800501</WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_DURATION>
<WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_START_OFFSET>1450</WMS_CONTENT_DESCRIPTION_PLAYLIST_ENTRY_START_OFFSET>
<WMS_CONTENT_DESCRIPTION_SERVER_BRANDING_INFO>WMServer/9.0</WMS_CONTENT_DESCRIPTION_SERVER_BRANDING_INFO>
</ContentDescription>
</XML>

```

The following is an example of how a Legacy Log may appear as sent to a Web server.

```

MX_STATS_LogLine: 0.0.0.0 2000-06-14 01:18:58 -
mmsu://foo.microsoft.com/testfile.wma 30 1 1 200 {35301A88-93D3-4F3A-
A284-30F7A611CD23} 7.0.0.1938 en-US - - wmplayer.exe 7.0.0.1938
Windows_2000 5.0.0.2195 Pentium 225 4551684 1528 mms UDP - - - - 29868
- 4 0 0 0 0 0 0 0 100 172.29.237.102 - - -

```

3.2 Defining Custom Namespaces in an XML Log

An .asx file (for more information, see [\[MSDN-WMMETA\]](#)) can be used to append log data to the XML log structure. Vendors may define any number of custom namespaces and name-value pairs in the "client-logging-data" structure, as specified in section [2.4](#), following the Content Description structure.

The following example illustrates how to add the **cs-media-role** field (section [2.1.30](#)) by using an .asx file.

```

<ASX version="3.0">
  <ENTRY>
    <TITLE> My Title </TITLE>
    <Author> My Author </Author>
    <PARAM name="log:cs-media-role" value="Advertisement" />
    <REF href="http://www.foo.MyDomain.com/live" />
  </ENTRY>
</ASX>

```

The additional and/or custom logging information is specified through the use of the PARAM element. To use the PARAM element in this way, the NAME attribute is set to "log:" followed by a log field name and a corresponding VALUE attribute. The log field specified in the NAME attribute is set to the value of the VALUE attribute. If the log does not already contain a field with the specified name, it will be added.

An XML namespace has to be defined for each custom log field specified in an .asx file. This namespace is appended to the NAME attribute and is separated from the field name by a second colon (":"). Because everything after the second colon is treated as a namespace, the field name should not contain a colon.

The following example illustrates the specification of custom log fields using an .asx file.

```
<ASX version="3.0">
  <ENTRY>
    <TITLE> My Title </TITLE>
    <Author> My Author </Author>
    <PARAM name="log:vendor-field1:VendorNameSpace" value="Value1" />
    <PARAM name="log:vendor-field2:VendorNameSpace" value="Value2" />
    <REF href="http://www.foo.MyDomain.com/live" />
  </ENTRY>
</ASX>
```

When an XML log is sent to a server for this .asx file, the new namespace is inserted after the Content Description section, as shown in the following example (many log fields extraneous to this example have been omitted for brevity and clarity).

```
<XML>
  <Summary>0.0.0.0 2003-09-27 00:27:24 ... </Summary>
  <c-ip>0.0.0.0</c-ip>
  <date>2003-09-27</date>
  <time>00:27:24</time>
  ...
  <ContentDescription>
    ...
  </ContentDescription>
  <VendorNameSpace>
    <vendor-field1>Value1</vendor-field1>
    <vendor-field2>Value2</vendor-field2>
  </VendorNameSpace>
</XML>
```

3.3 Example Streaming Log Messages

The following is an example of a [Streaming Log](#) in XML format.

```
<XML>
<Summary>0.0.0.0 2006-05-01 21:34:01 -
http://foo.microsoft.com/content.wmv 4 0 1 200 {3300AD50-2C39-46c0-
AE0A-3E0B6EFB86DC} 10.0.0.3802 en-US
Mozilla/4.0_(compatible;_MSIE_6.0;_Windows_NT_5.1)_ (WMFSDK/10.0.0.3802)
```

```

_WMPPlayer/10.0.0.4019 http://bar.microsoft.com iexplore.exe
6.0.2900.2180 Windows_XP 5.1.0.2600 Pentium 130 638066 - http TCP - - -
-0 - 0 0 0 0 0 0 0 0 0 100 - - - -
http://foo.microsoft.com/content.wmv - -</Summary>
<c-ip>0.0.0.0</c-ip>
<date>2006-05-01</date>
<time>21:34:01</time>
<c-dns>-</c-dns>
<cs-uri-stem>http://foo.microsoft.com/content.wmv</cs-uri-stem>
<c-starttime>4</c-starttime>
<x-duration>0</x-duration>
<c-rate>1</c-rate>
<c-status>200</c-status>
<c-playerid>{3300AD50-2C39-46c0-AE0A-3E0B6EFB86DC}</c-playerid>
<c-playerversion>10.0.0.3802</c-playerversion>
<c-playerlanguage>en-US</c-playerlanguage>
<cs-User-
Agent>Mozilla/4.0_(compatible;_MSIE_6.0;_Windows_NT_5.1)_(WMFSDK/10.0.0.3802)_WMPPlayer/10.0.0
.4019</cs-User-Agent>
<cs-Referer>http://bar.microsoft.com</cs-Referer>
<c-hostexe>iexplore.exe</c-hostexe>
<c-hostexever>6.0.2900.2180</c-hostexever>
<c-os>Windows_XP</c-os>
<c-osversion>5.1.0.2600</c-osversion>
<c-cpu>Pentium</c-cpu>
<filelength>130</filelength>
<filesize>638066</filesize>
<avgbandwidth>-</avgbandwidth>
<protocol>http</protocol>
<transport>TCP</transport>
<audiocodec>-</audiocodec>
<videocodec>-</videocodec>
<c-channelURL>-</c-channelURL>
<sc-bytes>-</sc-bytes>
<c-bytes>0</c-bytes>
<s-pkts-sent>-</s-pkts-sent>
<c-pkts-received>0</c-pkts-received>
<c-pkts-lost-client>0</c-pkts-lost-client>
<c-pkts-lost-net>0</c-pkts-lost-net>
<c-pkts-lost-cont-net>0</c-pkts-lost-cont-net>
<c-resendreqs>0</c-resendreqs>
<c-pkts-recovered-ECC>0</c-pkts-recovered-ECC>
<c-pkts-recovered-resent>0</c-pkts-recovered-resent>
<c-buffercount>0</c-buffercount>
<c-totalbuffertime>0</c-totalbuffertime>
<c-quality>100</c-quality>
<s-ip>-</s-ip>
<s-dns>-</s-dns>
<s-totalclients>-</s-totalclients>
<s-cpu-util>-</s-cpu-util>
<cs-url>http://foo.microsoft.com/content.wmv</cs-url>
</XML>

```

The following is an example of how a Streaming Log may appear as sent to a Web server.

```

MX_STATS_LogLine: 0.0.0.0 2000-06-14 01:18:58 -
mmsu://foo.microsoft.com/testfile.wma 30 1 1 200 {35301A88-93D3-4F3A-

```

```
A284-30F7A611CD23} 7.0.0.1938 en-US - - wmplayer.exe 7.0.0.1938
Windows_2000 5.0.0.2195 Pentium 225 4551684 1528 mms UDP - - - 29868
- 4 0 0 0 0 0 0 0 100 172.29.237.102 - - -
mmsu://foo.microsoft.com/testfile.wma - -
```

3.4 Example Rendering Log Messages

The following is an example of a [Rendering Log](#) in XML format.

```
<XML>
<Summary>0.0.0.0 2006-05-01 21:34:01 -
http://foo.microsoft.com/content.wmv 4 0 1 200 {3300AD50-2C39-46c0-
AE0A-3E0B6EFB86DC} 10.0.0.3802 en-US
Mozilla/4.0_(compatible;_MSIE_6.0;_Windows_NT_5.1)_(WMFSDK/10.0.0.3802)
_WMPlayer/10.0.0.4019 http://bar.microsoft.com iexplore.exe
6.0.2900.2180 Windows_XP 5.1.0.2600 Pentium 130 638066 - Cache -
Windows_Media_Audio_9 Windows_Media_Video_9 - - 0 - - - - - - - -
100 - - - - - http://foo.microsoft.com/content.wmv - - - 0
</Summary>
<c-ip>0.0.0.0</c-ip>
<date>2006-05-01</date>
<time>21:34:01</time>
<c-dns>-</c-dns>
<cs-uri-stem>http://foo.microsoft.com/content.wmv</cs-uri-stem>
<c-starttime>4</c-starttime>
<x-duration>0</x-duration>
<c-rate>1</c-rate>
<c-status>200</c-status>
<c-playerid>{3300AD50-2C39-46c0-AE0A-3E0B6EFB86DC}</c-playerid>
<c-playerversion>10.0.0.3802</c-playerversion>
<c-playerlanguage>en-US</c-playerlanguage>
<cs-User-Agent>Mozilla/4.0_(compatible;_MSIE_6.0;_Windows_NT_5.1)
_(WMFSDK/10.0.0.3802)_WMPlayer/10.0.0.4019</cs-User-Agent>
<cs-Referer>http://bar.microsoft.com</cs-Referer>
<c-hostexe>iexplore.exe</c-hostexe>
<c-hostexever>6.0.2900.2180</c-hostexever>
<c-os>Windows_XP</c-os>
<c-osversion>5.1.0.2600</c-osversion>
<c-cpu>Pentium</c-cpu>
<filelength>130</filelength>
<filesize>638066</filesize>
<avgbandwidth>-</avgbandwidth>
<protocol>Cache</protocol>
<transport>-</transport>
<audiocodec>Windows_Media_Audio_9</audiocodec>
<videocodec>Windows_Media_Video_9</videocodec>
<c-channelURL>-</c-channelURL>
<sc-bytes>-</sc-bytes>
<c-bytes>0</c-bytes>
<s-pkts-sent>-</s-pkts-sent>
<c-pkts-received>-</c-pkts-received>
<c-pkts-lost-client>-</c-pkts-lost-client>
<c-pkts-lost-net>-</c-pkts-lost-net>
<c-pkts-lost-cont-net>-</c-pkts-lost-cont-net>
<c-resendreqs>-</c-resendreqs>
<c-pkts-recovered-ECC>-</c-pkts-recovered-ECC>
<c-pkts-recovered-resent>-</c-pkts-recovered-resent>
```

```

<c-buffercount>-</c-buffercount>
<c-totalbuffertime>-</c-totalbuffertime>
<c-quality>100</c-quality>
<s-ip>-</s-ip>
<s-dns>-</s-dns>
<s-totalclients>-</s-totalclients>
<s-cpu-util>-</s-cpu-util>
<cs-url>http://foo.microsoft.com/content.wmv</cs-url>
</XML>

```

The following is an example of how a Rendering Log may appear as sent to a Web server.

```

MX_STATS_LogLine: 0.0.0.0 2000-06-14 01:18:58 -
mms://foo.microsoft.com/test.wma 30 1 1 200 {35301A88-93D3-4F3A-A284-
30F7A611CD23} 7.0.0.1938 en-US - - wmplayer.exe 7.0.0.1938 Windows_2000
5.0.0.2195 Pentium 225 4551684 1528 Cache - - - - - 29868 - - - - -
- - - 100 - - - - mms://foo.microsoft.com/test.wma - -

```

3.5 Example Connect-Time Log Message

The following is an example of a [Connect-Time Log](#) message in XML format.

```

<XML>
<Summary></Summary>
<c-dns>-</c-dns>
<c-ip>0.0.0.0</c-ip>
<c-os>Windows</c-os>
<c-osversion>6.0.0.6000</c-osversion>
<date>2006-08-30</date>
<time>13:18:44</time>
<c-cpu>Pentium</c-cpu>
<transport>TCP</transport>
</XML>

```

3.6 Example Log Sent to a Web Server

The following is an example of a client validating a logging URL and subsequently transmitting a logging message to the Web server.

```

GET /scripts/wmsiislog.dll HTTP/1.1
User-Agent: NSPlayer
Host: WebServer:8080
Connection: Keep-Alive
Cache-Control: no-cache

HTTP/1.1 200 OK
Connection: close
Date: Wed, 27 Jun 2007 02:54:23 GMT
Server: Microsoft-IIS/6.0
Content-Type: text/html

<head><title>WMS ISAPI Log Dll/9.00.00.3372</title></head>

```

```
<body><h1>WMS ISAPI Log Dll/9.00.00.3372</h1></body>
```

```
POST /scripts/wmsiislog.dll HTTP/1.1
Content-Type: text/plain;charset=UTF-8
User-Agent: NSPlayer
Host: WebServer:8080
Content-Length: 424
Connection: Keep-Alive
Cache-Control: no-cache
```

```
MX_STATS_LogLine: .0.0.0.0 2007-06-27 02:52:39 - asfm://239.192.50.29:30864 0 39 1 200
{3300AD50-2C39-46c0-AE0A-0572F2EA5330} 10.0.0.4054 en-US
WMFSDK/10.0.0.4054_WMPlayer/10.0.0.4036 - wmplayer.exe 10.0.0.3802 Windows_XP 5.1.0.2600
Pentium 229 10413011 411536 asfm UDP Windows_Media_Audio_9.2 -
http://WebServer:8080/multicast.nsc - 2170350 - 182 0 0 0 0 0 1 3 100 239.192.50.29 - -
- http://WebServer:8080/multicast.nsc - -
HTTP/1.1 200 OK
Server: Microsoft-IIS/6.0
Date: Wed, 27 Jun 2007 02:54:23 GMT
Connection: close
```

3.7 Parsing Windows Media Log Files

Microsoft Log Parser 2.2 is a tool that queries text-based data and other system data sources, including Windows Media log files. For more information, see [\[MSFT-LOGPARSER\]](#).

4 Security Considerations

A server that receives a logging message SHOULD validate the syntax of the fields. For example, the server should check that logging fields that are supposed to contain numerical data really do so, and that no invalid characters, such as control characters, are present. Invalid fields or characters could cause any tools that process the logging information to malfunction.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Windows NT® operating system
- Microsoft Windows® 2000 operating system
- Windows® XP operating system
- Windows Server® 2003 operating system
- Windows Vista® operating system
- Windows Server® 2008 operating system
- Windows® 7 operating system
- Windows Server® 2008 R2 operating system

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.5:](#) Windows Media Player 6.4 specifies the Internet host name in the **c-dns** field.

[<2> Section 2.1.10:](#) On Windows Vista and Windows 7, **c-os** is set to "Windows".

[<3> Section 2.1.25.2:](#) Windows Media Player 6.4, Windows Media Format 7.0 SDK, Windows Media Format 7.1 SDK, and Windows Media Player for Windows XP never specify status code 210.

[<4> Section 2.5.1:](#) Windows Media Player 6.4 specifies its own IP address in the **c-ip** field. Windows Media Format 7.0 SDK, Windows Media Format 7.1 SDK, and Windows Media Player for Windows XP specify their own IP address in the **c-ip** field depending on the current setting of a configuration value in the user interface.

[<5> Section 2.5.1:](#) Windows Media Player 6.4, Windows Media Format 7.0 SDK, Windows Media Format 7.1 SDK, and Windows Media Player for Windows XP never include the three optional fields.

[<6> Section 2.5.3:](#) Windows Media Format 9 Series SDK, Windows Media Format 9.5 SDK, Windows Vista, and Windows 7 do not include the "contentdescription" and "client-logging-data" syntax elements in the XML-format logging message when using RTSP [\[MS-RTSP\]](#).

[<7> Section 2.6.2:](#) Windows Media Format 9 Series SDK, Windows Media Format 9.5 SDK, Windows Vista, and Windows 7 do not include the "contentdescription" and "client-logging-data" syntax elements in the XML-format logging message when using RTSP [\[MS-RTSP\]](#).

[<8> Section 2.6.2:](#) When going through a proxy, Windows Media Services on Windows Server 2003 with SP1, Windows Server 2008 and Windows Server 2008 R2 duplicate the "<c-channelURL>",

"</c-channelURL>", "<cs-media-role>" and "</cs-media-role>" tags. For each tag that is duplicated, the duplicate tag immediately follows the original tag.

6 Change Tracking

This section identifies changes that were made to the [MS-WMLOG] protocol document between the May 2011 and June 2011 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1.2 References	Added explanatory statement regarding the removal of the publishing year from Microsoft Open Specification document references.	N	Content updated.

7 Index

A

[Applicability](#) 8
[audiocodec](#) 9
[avgbandwidth](#) 10

B

[Basic logging syntax](#) 30

C

[c-buffercount](#) 10
[c-bytes](#) 19
[c-channelURL](#) 19
[c-cpu](#) 10
[c-dns](#) 11
[Change tracking](#) 52
[c-hostexe](#) 11
[c-hostexeever](#) 11
[c-ip](#) ([section 2.1.8](#) 12, [section 2.1.9](#) 12)
[Connect-time log](#) 40
[c-os](#) 12
[c-osversion](#) 13
[c-pkts-lost-client](#) 13
[c-pkts-lost-cont-net](#) 13
[c-pkts-lost-net](#) 14
[c-pkts-received](#) 14
[c-pkts-recovered-ECC](#) 14
[c-pkts-recovered-resent](#) 15
[c-playerid](#) 15
[c-playerlanguage](#) 16
[c-playerversion](#) 16
[c-quality](#) 17
[c-rate](#) 17
[c-resendreqs](#) 18
[cs-media-name](#) 20
[cs-media-role](#) 20
[cs-Referer](#) 21
[c-starttime](#) 18
[c-status](#) 18
[cs-uri-stem](#) 22
[cs-uri](#) 21
[cs-User-Agent](#) 22
[cs-user-name](#) 23
[c-totalbuffertime](#) 19

D

[date](#) 23

E

Examples
 [legacy logging message example](#) 42
 [parsing Windows Media log files example](#) 48
[Extended logging syntax](#) 30

F

[Fields - vendor-extensible](#) 8
[filelength](#) 24
[filesize](#) 24

G

[Glossary](#) 6

I

[Informative references](#) 7
[Introduction](#) 6

L

Legacy log
 [common definitions](#) 34
 [overview](#) 34
 [sent to Web server](#) 36
 [W3C format](#) 35
 [XML format](#) 36
[Legacy logging message example](#) 42
[Localization](#) 8
[Log data fields](#) 9
[Logging message - W3C syntax](#) 29
[Logging message - WXML schema](#) 32
[Logging message sent to Web servers](#) 30

N

[Normative references](#) 6

P

[Parsing Windows Media log files example](#) 48
[Product behavior](#) 50
[protocol](#) 24

R

References
 [informative](#) 7
 [normative](#) 6
[Relationship to other protocols](#) 8
Rendering log
 [common definitions](#) 38
 [overview](#) 38
 [sent to Web server](#) 40
 [sent to Windows Media Services](#) 39

S

[sc-bytes](#) 27
[s-content-path](#) 25
[s-cpu-util](#) 25

- [s-dns](#) 25
- [Security](#) 49
- [s-ip](#) 26
- [s-pkts-sent](#) 26
- [s-proxied](#) 26
- [s-session-id](#) 27
- [Status Code 200 \(No Error\)](#) 19
- [Status Code 210 \(Client Successfully Reconnected\)](#) 19
- [s-totalclients](#) 27
- Streaming log
 - [common definitions](#) 36
 - [overview](#) 36
 - [sent to Web server](#) 38
 - [sent to Windows Media Services](#) 38
- Structures
 - [connect-time log](#) 40
 - [legacy log](#) 34
 - [log data fields](#) 9
 - [logging message - W3C syntax](#) 29
 - [logging message - XML schema](#) 32
 - [logging message sent to Web servers](#) 30
 - [overview](#) 9
 - [rendering log](#) 38
 - [streaming log](#) 36

T

- [time](#) 28
- [Tracking changes](#) 52
- [transport](#) 28

V

- [Vendor-extensible fields](#) 8
- [Versioning](#) 8
- [videocodec](#) 28

X

- [x-duration](#) 29